NTM02

24 Hour/7 Day Compact Digital Module



Features & Benefits

- 4 ON/4 OFF Easy-Set Programme Periods Per Day
- 28 ON/28 OFF Programmes Per Week
- Minimum Switching Time - 1 minute
- Extra Large ‘Easy View’ Screen with Blue LED Backlighting
- Red LED ‘Mains ON’ and green LED ‘Output’ indicators for easy viewing
- Self-Cancelling Override Button to Next Programme Change
- Optional 1 and 2 Hour Boost Button
- Automatic Summer/Winter Time Change

Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	OEM (Panel Mount)
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C
Setting Type	Digital
Battery Type	NiMH 1.2V 80mAh Recharable Battery
Power Reserve	672 Hours (28 Days)
Program Modes	24 Hour/7 Day, 1 Hour/2Hour Boost
Voltage Free Contacts	Normally Open, Normally Closed (Changeover)
Mounting Hole Centres (mm)	54

Standby Consumption	<0.96W
Number of Channels	1
Switch rating	16A Resistive, 4A Inductive, 1HP Motor, 750W Halogen/Fluorescent, 100W CFL, 100W LED
Shortest Switching Time	1 Minute
Programmable Slots	4 ON 4 OFF
Permanent ON Facility	Yes (Override ON)
Cable Entry(s)	Bottom Entry (Spade Connector)

General

Weight (g)	89
Height (mm)	60
Width (mm)	60
Depth (mm)	34
Body Construction	Polycarbonate
Product Colour	White
EAN Number	5012483012215
Guarantee Period	3 Years
Trade Tariff Commodity Code	9032890090

Line Diagrams

