Distribution Box 4/32 IP 44 4x LS 230 V/16 A, 1xLS 400 V/16 A, 1xFI 40 A 4-polig 30 mA

For constant use outdoors, IP 44.









IP44 FI-SAFETY

Product number 1154890020
EAN 4007123650361

DESCRIPTION

- Robust, break and impact resistant plastic casing.
- Suitable for robust wall mounting.
- With an ergonomic carrying handle for comfortable carrying.
- Pre-wired and ready for connection.
- Protective cover for fuses.
- With RCD circuit breaker 30 mA for extra safety.
- Earthed sockets 230 V with 3 phases.

TECHNICAL DATA

Max. current carrying capacity	32 A
Miniature circuit breaker	5
Residual current circuit breaker (RCCB)	FI with IFN 0.03 A (standard)
Rated current (FI)	30 mA
Number of poles (FI)	4
CEE 400 V / 16 A / 3P+N+PE (5p) Steckdosen	1
CEE 400 V / 32 A / 3P+N+PE (5p) Steckdosen	1
Earthed socket outlets	4
Plug system socket	Type F (Protective contact)
Supply/ connection option	Attachment plug
Plug system plug	CEE 32 A 3P+N+E (5p) 400 V
Degree of protection (IP)	IP44

PACKAGING, DIMENSIONS AND WEIGHTS

Packaging	Coloured sales box
UP	1
Weight of product (without packaging)	3.46 kg
Dimension LxWxH (without packing)	28 cm x 34.9 cm x 13 cm
Weight of product (including packaging)	3.81 kg
Dimension LxWxH (incl. packing)	38 cm x 29 cm x 14 cm