
RSM 50-10M
power cable – PVC Cable Jacket



Technical data

Type	RSM 50-10M
ID no.	U2083
Connector A	Male, 7/8"-16 UN, Straight
Number of Pins	4+PE
Contacts	Metal, CuZn, Gold-plated
Contact carriers	Plastic, TPU, Yellow
Connector body	Plastic, TPU, Yellow
Coupling nut/screw	Brass, CuZn, Nickel-plated
Mechanical lifespan	> 100 Mating cycles
Pollution degree	3
Type of protection	IP67, Only in screwed condition
Cable	
Cable diameter	Ø 7.6 mm ± 0.30
Cable length	10 m
Cable jacket	PVC, Yellow
Core insulation	PVC
Core cross-section	5 x 0.83 mm²
Arrangement of strands	19 x 0.25 mm
Core colors	BN, WH, BU, BK, GNYE
Electrical properties at +20 °C	
Rated voltage	600 V
Current	9 A
Mechanical and chemical properties	
Bending radius (stationary installation)	≥ 5 x Ø
Bending radius (flexible use)	≥ 10 x Ø
Ambient temperature range (stationary)	-40 °C…+105 °C

Features

- Power cable: 5 x 0.83 mm², 5 x 18 AWG
- Jacket material: PVC
- Jacket color: yellow
- Jacket diameter: 7.6 mm
- UV-resistant
- Flame-retardant acc. to CSA FT4
- UL, CSA approval
- RoHS-compliant
- Protection class: NEMA 1, 3, 4, 6P and IEC IP67
- Open end
- 7/8" male, straight
- Cable length: 10 m

Contact assignment



Circuit Diagram



RSM 50-10M | 13-10-2021 19-53 | Technical modifications reserved

Technical data

Other Featues	
UV resistance	yes
Flame-retardant	yes

RSM 50-10M | 13-10-2021 19-53 | Technical modifications reserved