Date: 11/04/2023

Digital indicator model DI30

Digital indicator model DI30

Item number:	12458741
Quantity:	1 pcs.
Order code:	DI30-S-HO5ZB-ZZZZZZ
Overview:	Digital indicator model DI30 Input: 0 ... 5/10 V, 0/4 ... 20 mA Alarm output: 2 relays (AC 230V 5A, DC 30V 5A), free adjustable Supply voltage for transmitter: DC 24 V max. 50 mA Power supply: AC 230 V, 50/60 Hz for wall mounting with enclosure; IP65 Input: without Configuration measuring range start value: without Configuration measuring range end value: without Additional configuration details: without
Details:	Digital indicator model DI30 Specifications according to data sheet: AC 80.05 Dimensions: 96 x 96 x 71 mm Display: LED, 4 digit from -999 ... 9999 Accuracy of reading: +/- 0.1% of span +/- 1 digit Input: 0 ... 5/10 V, 0/4 ... 20 mA Alarm output: 2 relays (AC 230V 5A, DC 30V 5A), free adjustable Supply voltage for transmitter: DC 24 V max. 50 mA Electrical connection: via screw terminals Power supply: AC 230 V, 50/60 Hz mounting and ingress protection: for wall mounting with enclosure; IP65 Instrument configuration: factory adjustment, device will be configured by the operator Configuration measuring range start value: without Configuration measuring range end value: without Additional configuration details: without Input: without Special design features: without

© 2023 - WIKA Instruments s.a.r.l.