MULTI-PURPOSE

SKYTEC® | ARIA™

NITRILE FOAM PALM WITH 3D MOISTUREVAP BREATHABILITY

Excellent resistance to abrasion. Outstanding durability and grip.

FEATURES

- Level 4 abrasion resistance
- Superior comfort and dexterity
- Anatomically engineered for maximum fit
- Excellent grip in both wet and dry environments
- An Oeko-Tex™ certified product
- Seamless nylon/spandex liner
- Patented nitrile foam palm coating enhances protection
- Sanitized® antimicrobial finish provides extra freshness
- Light thermal protection up to 100°C for a short period
- Touchscreen capabilities to allow usage with screen devices



3D MOISTUREVAP | Sanitized Actifresh | CONFIDENCE IN TEXTILES Tested for harmful substances according to Oeko-Tex® Standard 100 | TOUCH SCREEN

SUITABLE FOR

Typical Industries

- Automotive
- Logistics
- Maintenance
- Manufacturing
- Oil and Gas
- Utilities

Suitable Applications

- Assembly
- Goods Handling
- Light Fabrication
- Quality Inspection
- Warehousing

CERTIFICATION

	CAT II	EN 388:2016	EN407:2004	ANSI	ANSI
UKCA	CE	4131X	X1XXXX	4 ABRASION	2 PUNCTURE

See overleaf for explanation

Globus GROUP

SKYTEC® ARIA™

PRODUCT INFORMATION

MATERIALS	LINER:	15 gauge nylon, spandex
	COATING:	Foam nitrile
COLOUR	Grey / Black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- USE: General handling glove. Not suitable for thermal, electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	SKY491 SKY492 SKY493 SKY494 SKY495	10 pairs per bag 120 pairs per case

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4 0-5 0-4 0-4 A-F P

- 0-4: Abrasion Resistance
- 0-5: Circular Blade Cut Resistance
- 0-4: Tear Resistance
- 0-4: Puncture Resistance
- A-F: Straight Blade Cut Resistance (EN ISO: 13997)
- P: Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

HEAT AND FIRE
EN 407

PERFORMANCE LEVELS
0-4 0-4 0-4 0-4 0-4 0-4

- 0-4: Burning Behaviour
- 0-4: Contact Heat Resistance
- 0-4: Convective Heat Resistance
- 0-4: Radiant Heat Resistance
- 0-4: Resistance to Small Drops Of Molten Metal
- 0-4: Resistance to Large Splashes of Molten Metal

ANSI/ISEA 105-2016 ABRASION RATING CHART

Abrasion Level Rating	0	1	2	3	4	5	6
Gram Load	500	500	500	500	1000	1000	1000
Abrasion Cycles to Fail	<100	≥100	≥500	≥1,000	≥3,000	≥10,000	≥20,000

ANSI/ISEA PUNCTURE RESISTANCE

ANSI Puncture Level	Puncture Resistance (newtons)
1	10–19
2	20–59
3	60–99
4	100–149
5	150+

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

GLOBUS AMERICAS
www.globusgroup.com
E: americas@globusgroup.com

Globus GROUP

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES
Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2022 Globus (Shetland) Ltd | SKY-DATA-ARIA-0922_1

EU Type-Examination Certificate issued by SATRA Technology Europe Limited. Bracetown Business Park. Clonee. D15YN2P. Republic of Ireland. (Notified Body No. 2777).
UKCA Type-Examination Certificate issued by SATRA Technology Centre Ltd., Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom (Approved Body No. 0321)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.