Specifications

Eaton 248862



Catalog Number: 248862

Eaton Distribution parts. Auxiliary contact, 1N/O+1N/C

General specifications

Product Name	**Catalog Number**
Eaton Distribution parts	248862
EAN	**Product Length/Depth**
4015082488628	87.5 mm
Product Height	**Product Width**
60 mm	8.75 mm
Product Weight	**Compliances**
0.026 kg	RoHS conform

Powering Business Worldwide

Product specifications

Equipment heat dissipation, current-dependent

0 W

Voltage type

AC

Functions

Auxiliary switch

Static heat dissipation, non-current-dependent

0 W

Additional equipment required

Auxiliary switch

Ambient operating temperature - max

60 °C

Ambient operating temperature - min

-40 °C

Assembly width

0.5 TE

Heat dissipation per pole, current-dependent

0.5 W

Main contact unit current rating - max

63 A

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

1

Number of contacts (normally open contacts)

1

Number of poles at main contact unit - max

4

Number of switches (fault signal)

0

Rated operational current for specified heat dissipation (In)

3 A

Rated operational voltage (Ue) - max

230 V

Rated switch current

Resources

Declarations of conformity

DA-DC-03_Z-S

DA-DC-03_Z-S_SC_SB

DA-DC-03_Z-SC

Drawings

eaton-wiring-diagram-z-sc.jpg

eaton-mcb-dimensions-122x132.eps

eaton-dimensions-ma-sch40.jpg

3 A

Device fitting

Auxiliary switch / relay

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia