DATASHEET - SWD4-SF4P-67

MB-Power plug-in connection for round cables SWD4-LR4P, plug 7/8", IP67

Part no. **SWD4-SF4P-67**
183228

General specifications	
Product name	Eaton SWD4 Accessory Plug-in connection
Part no.	SWD4-SF4P-67
EAN	4015081781614
Product Length/Depth	102.564 millimetre
Product height	12.821 millimetre
Product width	51.282 millimetre
Product weight	0.082 kilogram
Certifications	UL CSA
Product Tradename	SWD4
Product Type	Accessory
Product Sub Type	Plug-in connection
Catalog Notes	not relevant
General information	
Degree of protection	IP67 IP67 (according to IEC/EN 60529, EN 50178, VBG 4)
Product category	SmartWire-DT accessories
Type	Plug connector for 4 pole SWD4-…LR4P-.. round cables
Ambient conditions, mechanical	
Mounting position	As required
Climatic environmental conditions	
Air pressure	795 - 1080 hPa (operation)
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	80 °C
Ambient storage temperature - min	-40 °C
Ambient storage temperature - max	80 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-3 Dry heat to IEC 60068-2-2
Environmental conditions	Condensation: permissible
Operating temperature - min	-25 °C
Operating temperature - max	80 °C
Electrical rating	
Power loss	0 W
Communication	
Connection to SmartWire-DT	Yes
Connection type	Screw connection
Design verification	
Heat dissipation capacity Pdiss	0 W
Static heat dissipation, non-current-dependent Pvs	0 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.

10.3 Degree of protection of assemblies	Meets the product standard's requirements.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Programmable logic controllers PLC (EG000024) / Accessories/spare parts for controls (EC002584)	
Electric engineering, automation, process control engineering / Display and control component / Panel (HMI) / Panel (HMI, accessories) (ecl@ss13-27-33-02-92 [AFX005008])	
Type of electrical accessory/spare part	Plug
Type of mechanical accessory/spare part	Other
Accessory	Yes
Spare part	No

© 04/2023 by Eaton Industries GmbH