DATASHEET



IFL 70-385-11P

- Design 385

Data

Ordering data

Product type description	IFL 70-385-11P
Article number (order number)	101116724
EAN (European Article Number)	4030661022048
eCl@ss number, version 12.0	27-27-40-01
eCl@ss number, version 11.0	27-27-01-01
eCl@ss number, version 9.0	27-27-01-01
ETIM number, version 7.0	EC002714
ETIM number, version 6.0	EC002714

General data

Standards	DIN VDE 0660-208 EN IEC 60947-5-2
Housing construction form	Block
Installation conditions (mechanical)	not flush
Housing material	Plastic
Gross weight	416 g

General data - Features

Integral system diagnostics, status	Yes
Number of cable wires	4

Mechanical data - Switching distances according EN IEC 60947-5-3

Nominal switching distance S_n	70 mm

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
Cable section, maximum	2 x 1.5 mm²

Mechanical data - Dimensions

Length of sensor	40 mm
Width of sensor	80 mm
Height of sensor	135 mm

Ambient conditions

Degree of protection	IP67
Ambient temperature	-25 ... +70 °C
Protection class	II

Electrical data

No-load supply current I_0, typical	5.5 mA
Rated operating voltage	10 ... 60 VDC
Operating current	400 mA
Switching element	NO contact and NC contact (antivalent)
Protection circuit integrated	inductive interference protection Protection against polarity reversal
Switching frequency, approx.	25 Hz

Type of voltage range	DC

Electrical data - Digital Output

Voltage drop U_d, maximum	1.5 V
Current at Voltage drop U_d	0.4 A
Design of control elements	p-type

Status indication

Note (Integral System Diagnostics, status)	yellow LED

Note

Note (General)	Mounting angle HW 385-1 to simplify mounting available

Ordering code

Product type description:
IFL (1)-(2)-(3)(4)(5)(6)(7)

(1)

50	Switching distance 50 mm

(2)

385	Square design, 135 x 80 x 40 mm

(3)

01	Opener (NC)
10	Normally open contact (NO)
10/01	NO contact / NC contact with wiring compartment
11	1 NO contact / 1 NC contact antivalent

(4)

without	Cable

D	DC 2-wire

(5)

Z	Protection class IP67

(6)

N	n-type
P	p-type

(7)

2130	Can be used up to +130 C, without LED switching conditions display

Pictures

Product picture (catalogue individual photo)



ID: kifl5f07
| 1.0 MB | .jpg | 352.778 x 529.167 mm - 1000 x 1500 px - 72 dpi
| 83.9 kB | .png | 74.083 x 111.125 mm - 210 x 315 px - 72 dpi
| 69.3 kB | .jpg | 82.197 x 123.472 mm - 233 x 350 px - 72 dpi