Practical and completely safe



- **Each fuse carrier is designed to take:**
  - a blow-out indicator
  - a padlock
- **Cartridge totally visible**
- **Class II insulation along the entire length of the carrier**



102 63



103 06

Miniature type 5 x 20

Instant reaction fuse - Ceramic body
Conform to IEC 60127 - NF EN 60127 - VDE 0820-1
High rupture capacity (A)
For use with dimmers, Viking terminals and emergency lighting units

Pack	Cat. No.	Rating (Amps)	Voltage~ (Volts)	Rupture capacity (Amps)
10	102 02	0.2		
10	102 05	0.5		
10	102 06	0.63		
10	102 10	1.0		
10	102 12	1.25		
10	102 16	1.6		
10	102 20	2.0	250	1500
10	102 25	2.5		
10	102 30	3.15		
10	102 50	5.0		
10	102 63	6.3		
10	102 96 (1)	10.0	250	500

Cylindrical - without indicator

Pack	Cat. No.	Rating (Amps)	Voltage~ (Volts)	Rupture capacity (Amps)	Protected section (mm2) Copper
		6.3 x 23			
10	103 06 (1)	6	230	6 000	1.5
		8.5 x 23			
10	113 02	2			
10	113 04	4			
10	113 06	6	230	6 000	1.5
10	113 10	10			
		10.3 x 25.8			
10	116 06 (2)	6			
10	116 10 (2)	10	230	6 000	2.5
10	116 16 (2)	16			
		8.5 x 31.5			
10	123 01	1			
10	123 02	2			
10	123 04	4			
10	123 06	6			
10	123 08	8	400	20 000	2.5
10	123 10	10			
10	123 12	12			
10	123 16	16			
10	123 20	20			
		10.3 x 31.5			
10	126 16	16			
10	126 20	20	400	20 000	4
10	126 25	25			
		10.3 x 38			
10	133 32	32	400	20 000	6
		Neutral links			
10	123 00	8.5 x 31.5			
10	133 00	10 x 38			

(1) Overrating not described by standards
(2) Conform to BS 1361 (1971)

HRC cartridge fuses


120 04


133 08


143 10


140 12


153 96


150 50

Technical data and dimensions (p. 46)

Cylindrical type gG

Pack	Cat. No.	
		Conform to NF C 63-210/211 - EN 60269-1, 2 and IEC 60269-1, 2 & 2-1 Veritas approved – without indicator
		10 X 38 mm – 500 V, 100 KA HRC
		Rating (amp)
10	133 94	0.5
10	133 01	1
10	133 02	2
10	133 04	4
10	133 06	6
10	133 08	8
10	133 10	10
10	133 12	12
10	133 16	16
10	133 20	20
10	133 25	25
		10.3 X 38 mm – 500 V, 20 KA HRC
10	133 32	32
		14 X 51mm – 500 V, 100 KA HRC
10	143 02	2
10	143 04	4
10	143 06	6
10	143 10	10
10	143 16	16
10	143 20	20
10	143 25	25
10	143 32	32
10	143 40	40
		14 X 51mm – 400 V, 100 KA HRC
10	143 50 (1)	50
		22 X 58mm – 500 V, 100 KA HRC
10	153 16	16
10	153 20	20
10	153 25	25
10	153 32	32
10	153 40	40
10	153 50	50
10	153 63	63
10	153 80	80
10	153 96	100
		22 X 58mm – 400 V, 100 KA HRC
10	153 97 (1)	125

Cylindrical type aM (motor rated)

Pack	Cat. No.	
		Conform to NF C 60-200 - EN 60269-1 IEC 60269-1 Veritas approved – without indicator (130 XX) Without striker (140 XX – 150 XX)
		10 X 38mm – 500 V, 100 KA HRC
		Rating (amp)
10	130 92	0.25
10	130 95	0.5
10	130 01	1
10	130 02	2
10	130 04	4
10	130 06	6
10	130 08	8
10	130 10	10
10	130 12	12
10	130 16	16
		10 X 38mm – 400 V, 100 KA HRC
10	130 20 (2)	20
10	130 25 (2)	25
		14 X 51mm – 500 V, 100 KA HRC
10	140 02	2
10	140 04	4
10	140 06	6
10	140 08	8
10	140 10	10
10	140 12	12
10	140 16	16
10	140 20	20
10	140 25	25
10	140 32	32
10	140 40	40
		14 X 51mm – 400 V, 100 KA HRC
10	140 45 (1)	45
10	140 50 (1)	50
		22 X 58mm – 500 V, 100 KA HRC
10	150 16	16
10	150 20	20
10	150 25	25
10	150 32	32
10	150 40	40
10	150 50	50
10	150 63	63
10	150 80	80
10	150 96	100
		22 X 58mm – 400 V, 100 KA HRC
10	150 97	125
		Neutral links
10	123 00	8.5 X 31.5
10	133 00	10.3 X 38
10	143 00	14 X 51
10	153 00	22 X 58

(1) Overrating described by standards
(2) Overrating not described by standards

Some items sold separately
For pack quantity, please refer to numerical index pages
For trade price, please see your local HPM Legrand representative for the current price list