Date: 24/04/2023

232.30.100 10 bar G1/2B lower mount

Bourdon Tube Pressure Gauges, Safety Pattern

Item number:	9030654
Quantity:	1 pcs.
Order code:	232.30-E-BG410Z-GD-UZHZCZZ-ZZZZZZZ 213D31ZI3W0 Z2Z-IZZZZZZ12ZZZ LABEL-PG1DE-ZZZZZ
Overview:	232.30.100 10 bar G1/2B lower mount Measuring System 316L Ingress protection: IP 65 class 1.0 Window: laminated safety glass Permissible medium temperature: + 200 °C Permissible ambient temperature: -40 … +60 °C Pressure Gauge Standard: International (standard Europe) *WIKA* with Serial number Label: WIKA standard without / with Tag-number
Details:	Bourdon Tube Pressure Gauges, Safety Pattern Series EN 837-1 Model: 232.30 Specifications according to data sheet: PM 02.04 Measuring system: stainless steel Case filling: without Nominal size: 100 mm Measuring range: gauge pressure range Scale range: 0...10 bar Process connection: G 1/2 B Connector location: lower mount Window: laminated safety glass Pointer: standard pointer Accuracy class: class 1.0 Overpressure safe: standard Case material: Stainless steel 1.4301 Case surface: bare Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress protection: IP 65 Permissible medium temperature: + 200 °C Permissible ambient temperature: -40 … +60 °C Movement: stainless steel Packaging: single packing Pressure Gauge Standard: International (standard Europe)

© 2023 - WIKA Instruments s.a.r.l.

Date: 24/04/2023

Manufacturer logo: *WIKA*
with Serial number
Permissible ambient temperature: -40 … +60 °C

© 2023 - WIKA Instruments s.a.r.l.