Rittal – The System.

Faster – better – everywhere.

Connection adaptor – SV 9342.210

Date : Oct 26, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Connection adaptor – SV 9342.210

created: 26.10.2021 on www.rittal.com/com-en



Product description

Material:	Cover: ABS Punched section: Polyamide Chassis 3439.010: Fibreglass-reinforced, thermoplastic polyester (PBT) Fire protection corresponding to UL 94-V0 Punched section: Polyamide
Colour:	RAL 7035
Note:	The technical data may vary for UL applications UL approval only applies in conjunction with AC application The rated operating voltage for DC applications depends on the busbar arrangement in the busbar supports 9340.050/9341.050/9342.050.

Product description

To fit busbars:	with cross-section height: 5 mm with cross-section height: 10 mm
Number of poles:	3-pole
For bar systems with centre-to-centre spacing:	60 mm
Dimensions:	Width: 20 mm Height: 215 mm
Rated current max.:	63 A
Rated operating voltage:	690 V, 3~

Connection for round conductor cross-sections:	fine wire with wire end ferrule: 2,5 mm² - 10 mm² multi-wire: 2,5 mm² - 10 mm² solid: 2,5 mm² - 10 mm²
Cable outlet:	Bottom
Packs of:	1 pc(s).
Weight/pack:	0.22 kg
Copper weight (kg per piece):	0.02
EAN:	4028177503601
Customs tariff number:	85369010
ETIM 7.0:	EC001531
ETIM 6.0:	EC001531
eCl@ss 8.0/8.1:	27370304
eCl@ss 6.0/6.1:	27370304
Product description:	SV Connection adaptor, 63 A, 690 V, 3-pole, cable outet bottom, round conductor connection 2,5-10 mm²

Approvals

Approvals:	ABS C-UL DNV-GL Lloyds Register of Shipping UL + C-UL
Certificates:	EAC
Declarations:	Declaration of conformity