Technical Data Sheet

Document Reference	125
Date of Issue	23rd Oct 2024
Revision Number	001
Date of Last Revision	23rd Oct 2024

125
Economy Retractable Pen



Technical Data Sheet Applicable To:

125-P01-I01	Economy Pen with Clip Blue
125-P01-I02	Economy Pen with Clip Black
125-P01-I03	Economy Pen with Clip Red
125-P01-I04	Economy Pen with Clip Green

Industry Usage
These retractable economy pens are ergonomic, with ridges at the point of grip, and come in four different ink colours

Features and Benefits
- Metal Detectable & X-ray Visible
- Refillable – refill available
- Blue housing only

Material Information:

- Length: 135.60mm (5.33″)
- Pen Thickness: 10.74mm (0.42″)
- Pen Thickness with clip: 18.81mm (0.74″)
- Carrier polymer: PP
- Addition Rate: 100%
- Heat stability: 280°c (536°f)
- Light fastness: 7-8 ISO 4892 (Blue Wool Scale)
- Weather Stability: 4-5 ISO 4892 (ISO 105-A002)
- Heavy Metals: NO
- Dairylide: NO
- Additive: YES

Compliance Information:
We confirm that the above-mentioned products are suitable for use in contact with all food types and are in conformity with the applicable requirements of the following regulations and standards:

- Regulation (EC) no. 1935/2004 on Materials and Articles intended to come into contact with food.
- Commission Regulation (EU) No 10/2011 on Plastic materials intended to come into contact with food including it's updates Regulation 1282/2011 and Regulation 1183/2012.
- Regulation (EC) No. 2023/2006 on Good Manufacturing Practice for materials and articles intended to come into contact with food.
- Council of Europe Resolution AP 89/1 on the use of Colorants in Plastic Materials coming into contact with food.
- US FDA 21 CFR 177.1520 (Olefin polymers) with colorants and additives cleared for use through listing in 178.3297 (Colorants for polymers), 178/2010 (antioxidants and/or stabilisers for polymers, or other respective parts of the FDA regulations)

Migration test data obtained under short term-repeat use test condition (6dm2/kg food) has demonstrated that levels of overall migration and specific migration of additives from these products will not exceed the legal limits with all food types.

Test Simulants	Food Types	Testing Condition
A-C, D1, D2 of Regulation No. 10/2011 for Plastic Materials and Articles in contact with food.	All dry, aqueous, acidic, alcoholic and fatty foods	2 hours at 70c, Repeat use. Test OM3 of regulation 10/2011

Dual-use food additives may be present but any migration into food will be minimal.

This compliance statement is based on information supplier by the polymer and pigment manufacturers, migration testing according to Regulation 10/2011, migration modelling and quality control systems in place at Detectamet.

REACH – No substances of very high concern (SVHC) above the 0.1% weight (w/w) threshold limit are present in the materials.

General Information:
Maximum use temperature: 100°c (212°f)
Maximum wash temperature: 121°c (249.8°f)
Maximum use temperature: Do not store at deep freeze temperatures prior to use.
No warranty is given or implied with respect to this information or patent infringement. Detectamet Ltd do not accept liability for loss or damage arising from the use of this information. Results are based on a test sample, our general experience and information from suppliers. Data and results may be confirmed by the buyer by testing for its intended conditions of use.
Safety You Detect
detectamet.global