Date: 11/04/2023

ERV1/2"-VU-L133/8-V29A-5PVC

ERV1/2"-VU-L133/8-V29A-5PVC

Item number: 48792388

Quantity: 1 pcs.

Order code: FLS-CBMZZ0010N1000DZM05HBZZ0108UZZZZZZZZZZNZZ
KAVCC01331ZZ

Overview:
ERV1/2"-VU-L133/8-V29A-5PVC
Float Switch Type FLS-ME
Material: Stainless steel 316Ti (EN 1.4571)
Pressure: 1 bar
Temperature range: -10°C up to 80°C
Fluid density: 1000 kg/m³
Electrical connection: Cable PVC 5 m
Process connection: Mounting thread upwards 1/2"BSP
Switch function 1: Change-over (SPDT) 108 mm
Switch rating: max. AC 50V; 5VA; 0.25A / DC 75V; 2,5W; 0.15A
Float: Stainless steel 316Ti V29A; Float outer diameter: 29 mm
Number of floats: 1 pc
Guide tube: OD 8 mm
Insertion length (L): 133 mm
Float stop: Welded peg

Float can't be mounted through the connection nozzle

Details:
ERV1/2"-VU-L133/8-V29A-5PVC
Float Switch Type FLS-ME
Material: Stainless steel 316Ti (EN 1.4571)
Pressure: 1 bar
Temperature range: -10°C up to 80°C
Fluid density: 1000 kg/m³
Electrical connection: Cable PVC 5 m
Process connection: Mounting thread upwards 1/2"BSP
Switch function 1: Change-over (SPDT) 108 mm
Switch rating: max. AC 50V; 5VA; 0.25A / DC 75V; 2,5W; 0.15A
Float: Stainless steel 316Ti V29A; Float outer diameter: 29 mm
Number of floats: 1 pc
Guide tube: OD 8 mm
Insertion length (L): 133 mm
Float stop: Welded peg

Float can't be mounted through the connection nozzle

© 2023 - WIKA Instruments s.a.r.l.