
20800-042 CONNECTOR KEYING/CODING CONTACT STRIP FOR ALL TYPES, EN 60603, DIN 41612



KEY FEATURES

- Use with plug-in units to avoid incorrect insertion
- For connectors in accordance with EN 60603 (DIN 41612)
- Needed space is front panel width: 4 HP: Type B, C, D, E, F, H
- Needed space of front panel width: 5 HP: Type E, G (Spacer element is required)
- 66 keying/coding possibilities if 2 keying/coding pins are used
- 924 keying/coding possibilities if 6 keying/coding pins are used

PRODUCT ATTRIBUTES

Product Type: Coding/Keying Indicator

ADDITIONAL PRODUCT DETAILS

Connector coding is used to provide security against incorrect insertion.

For connectors types E and G spacers are always required.

CERTIFICATIONS

RoHS COMPLIANT

North America
All locations
+1.763.422.2661
Chat with us:
schroff.nvent.com

Europe
Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
schroff.nvent.com

Asia
Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
schroff.nvent.com

Middle East & India
Dubai, United Arab Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
schroff.nvent.com

nVent

Our powerful portfolio of brands:
nVent.com **CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.