Date: 11/04/2023

ASC4RV1"-VSS-L400/8-V29A

ASC4RV1"-VSS-L400/8-V29A

Item number: 48793293

Quantity: 1 pcs.

Order code: FLS-CBMZZ0010N1000DZAZZGDZZ0315S0375SZZZZZNZZ KAVCC04002ZZ

Overview:

ASC4RV1"-VSS-L400/8-V29A
Float Switch Type FLS-MB
Material: Stainless steel 316Ti (EN 1.4571)
Pressure: 1 bar
Temperature range: -10°C up to 80°C
Fluid density: 1000 kg/m³
Electrical connection: Coupler plug 4 pin DIN 43650
Process connection: Mounting thread downwards 1"BSP
Switch function 1: Closing on rising level (SPST) 315 mm
Switch function 2: Closing on rising level (SPST) 375 mm
Switch rating: max. AC 50V; 10VA; 0.5A / DC 75V; 5W; 0.25A
Float: Stainless steel 316Ti V29A; Float outer diameter: 29 mm
Number of floats: 2 pcs
Guide tube: OD 8 mm
Insertion length (L): 400 mm
Float stop: Welded peg

Float fits through the connection nozzle

Details:

ASC4RV1"-VSS-L400/8-V29A
Float Switch Type FLS-MB
Material: Stainless steel 316Ti (EN 1.4571)
Pressure: 1 bar
Temperature range: -10°C up to 80°C
Fluid density: 1000 kg/m³
Electrical connection: Coupler plug 4 pin DIN 43650
Process connection: Mounting thread downwards 1"BSP
Switch function 1: Closing on rising level (SPST) 315 mm
Switch function 2: Closing on rising level (SPST) 375 mm
Switch rating: max. AC 50V; 10VA; 0.5A / DC 75V; 5W; 0.25A
Float: Stainless steel 316Ti V29A; Float outer diameter: 29 mm
Number of floats: 2 pcs
Guide tube: OD 8 mm
Insertion length (L): 400 mm
Float stop: Welded peg

Float fits through the connection nozzle

© 2023 - WIKA Instruments s.a.r.l.