Date: 22/01/2024

T15.H, Ex: Without, customer spec. Pt100, 3w, +0...+70°C

Digital temperature transmitter for resistance sensors T15

Item number:	46879562
Quantity:	1 pcs.
Order code:	T15.H-ZZZZZ-ZKK13C-P00000P00070-DZ000ZZ-ZZ A15 ZWIKA0W01SSZ
Overview:	T15.H, Ex: Without, customer spec. Pt100, 3w, +0...+70°C Specifications according to data sheet: TE 15.01 Configuration sensor: Pt100 Output signal: 4 ... 20 mA, 2-wire-design Tamb: Standard -40...85°C Transmitter Signalling of error: Down scale 3,5 mA
Details:	Digital temperature transmitter for resistance sensors T15 Specifications according to data sheet: TE 15.01 Output signal: 4 ... 20 mA, 2-wire-design Design: Head Explosion protection: Without Permissible ambient temperature transmitter: Standard -40...85°C Configuration: Customer's specification Configuration sensor: Pt100 Input configuration: 3-wire Unit: °C Measuring range start value - sign: Plus (incl. 0) Measuring range start value: 0 Measuring range end value - sign: Plus (incl. 0) Measuring range end value: 70 Transmitter Signalling of error: Down scale 3,5 mA

© 2024 - WIKA Instruments s.a.r.l.