Specifications

Eaton C22M125S

Catalog Number: C22M125S

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 400 Volts AC, 125 Amps,120 kA Breaking capacity, class aM, with striker, compatible with a CH22 Modular fuse holder



General specifications

Product Name
Eaton Bussmann series low voltage cylindrical fuse

Catalog Number
C22M125S

EAN
5027590495684

UPC
051712666886

Product Length/Depth
58 mm

Product Height
22 mm

Product Width
22 mm

Product Weight
54.8 g

Compliances
RoHS Compliant
CE Marked

Certifications
IEC 60269
EAC

Powering Business Worldwide

Electrical data

Amperage Rating

125 A

Voltage rating

400 V

Voltage type

AC

Breaking capacity

120 kA

Utilization category

aM (switchgear protection)

Frequency rating - max

62 Hz

Compatible fuse holder

Suitable for

CH22 Modular fuse holder

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

Declarations of conformity

CE C08G, C08M, etc cylindrical fuselinks

UKCA C08G, C08M, etc cylindrical fuselinks

Technical data sheets

720115 Cylindrical fuses

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia