PERFORMANCE MADE SMARTER



TC converter - isolated

3111

- Excellent accuracy, better than 0.05% of span
- Slimline housing of 6.1 mm
- Excellent EMC performance and 50/60 Hz noise suppression
- Selectable < 30 ms / 300 ms response time
- Pre-calibrated temperature ranges are selectable via DIP-switches

Application

- The 3111 temperature converter measures standard TC J and K temperature sensors, and provides an isolated analog voltage or current output.
- High 3 port isolation provides surge suppression and protects the control system from transients and noise.
- The 3111 can be mounted in the safe area or in Zone 2 / Division 2 areas.
- Approved for marine applications.


Technical characteristics

- Flexibly powered by 24 VDC (±30%) via power rail or connectors.
- < 30 ms fast response time with simultaneous sensor error detection when selected.
- Selectable 300 ms response time when signal dampening is needed.
- Selectable internal/external CJC.
- Excellent conversion accuracy in all available ranges, better than 0.05% of span.
- Meeting the NAMUR NE21 recommendations, the 3111 provides top measurement performance in harsh EMC environments.
- The device meets the NAMUR NE43 standard defining out of range and sensor error output values.
- A visible green LED indicates operational status of the unit and the input sensor.
- All terminals are protected against overvoltage and polarity error.
- High galvanic isolation of 2.5 kVAC.
- Excellent signal/noise ratio of > 60 dB.


Mounting / installation / programming

- Selectable DIP-settings for easy configuration of more than 1000 factory calibrated measurement ranges.
- The narrow 6.1 mm housing allows up to 165 units to be mounted per meter of DIN rail, without any air gap between units.
- Wide ambient temperature range of -25...+70°C.

Applications



Safe Area or
Zone 2 & Cl. 1, Div. 2, gr. A-D



This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

Order

Type	Version	
3111	With power rail connector / terminals	:-
	Supplied via terminals	:-N

Example: 3111-N

Environmental Conditions

Operating temperature..... -25°C to +70°C
Storage temperature..... -40°C to +85°C
Calibration temperature..... 20...28°C
Relative humidity..... < 95% RH (non-cond.)
Protection degree..... IP20
Installation in..... Pollution degree 2 & meas. / overvoltage cat. II

Mechanical specifications

Dimensions (HxWxD)..... 113 x 6.1 x 115 mm
Weight approx..... 70 g
DIN rail type..... DIN EN 60715/35 mm
Wire size..... 0.13...2.5 mm^2 / AWG 26...12 stranded wire
Screw terminal torque..... 0.5 Nm
Vibration..... IEC 60068-2-6
2...25 Hz..... ±1.6 mm
25...100 Hz..... ±4 g

Common specifications

Supply

Supply voltage..... 16.8...31.2 VDC
Max. required power..... 0.70 W
Max. power dissipation..... 0.70 W

Isolation voltage

Isolation voltage, test / working..... 2.5 kVAC / 300 VAC (reinforced)
Zone 2 / Div. 2..... 250 VAC

Response time

Response time (0...90%, 100...10%)..... < 30 ms / 300 ms (selectable)

Signal / noise ratio..... Min. 60 dB
Programming..... DIP-switches
Signal dynamics, input..... 23 bit
Signal dynamics, output..... 18 bit
Accuracy..... Better than 0.05% of selected range
EMC immunity influence..... < ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst..... < ±1% of span
Incorrect DIP-switch setting identification..... 0 V / 0 mA output; LED 0.5 s / 1 Hz

Input specifications

TC input

Temperature range, TC J..... -100...+1200°C
Temperature range, TC K..... -180...+1372°C
Min. measurement range (span) - TC J & K..... 50°C
Accuracy: the greater of..... Better than 0.05% of span or 0.5°C
Temperature coefficient: the greater of..... 0.1°C/°C or ≤ ±0.01%/°C
Sensor cable resistance..... < 5 kΩ per wire
Cold junction compensation (CJC): Accuracy @ external Pt100 input..... Better than ±0.15°C
Cold junction compensation (CJC): Accuracy @ internal CJC..... Better than ±2.5°C
Internal CJC error detection..... Yes
External CJC error detection..... Yes - selectable via DIP-switch
Open Thermocouple detection..... Yes - selectable via DIP-switch

Output specifications

Common output specifications

Updating time..... 10 ms

Current output

Signal range..... 0...23 mA
Programmable signal ranges..... 0 / 4...20 mA
Sensor error indication (0...20 mA)..... 0 mA or 23 mA / OFF
Sensor error indication (4...20 mA)..... 3.5 mA or 23 mA / acc. to NAMUR NE43 or OFF
Load (@ current output)..... ≤ 600 Ω
Load stability..... ≤ 0.01% of span / 100 Ω
Current limitation @ low output load..... < 60 mA peak / < 4 mA average

Voltage output

Programmable signal ranges..... 0/1...5 and 0/2...10 V
Sensor error indication..... 0 V / 10% above the max. / none

Open output..... < 18 V

I.S. / Ex marking

ATEX..... II 3 G Ex ec IIC T4 Gc
IECEx..... Ex ec IIC T4 Gc
FM, US..... Cl. I, Div. 2, Gp. A, B, C, D T4 or Cl. I, Zone 2, AEx nA IIC T4
FM, CA..... Cl. I, Div. 2, Gp. A, B, C, D T4 or Cl. I, Zone 2, Ex nA IIC T4
EAC Ex..... 2Ex nA IIC T4 Gc X

Observed authority requirements

EMC..... 2014/30/EU & UK SI 2016/1091
LVD..... 2014/35/EU & UK SI 2016/1101
ATEX..... 2014/34/EU & UK SI 2016/1107
RoHS..... 2011/65/EU & UK SI 2012/3032
ATEX..... 2014/34/EU
EAC..... TR-CU 020/2011
EAC Ex..... TR-CU 012/2011

Approvals

ATEX..... KEMA 10ATEX0147 X
IECEx..... KEM 10.0068X
UKEX..... DEKRA 21UKEX0055X
c FM us..... FM17US0004X / FM17CA0003X
c UL us, UL 61010-1..... E314307
DNV Marine..... TAA00001RW
EAC Ex..... RU C-DK.HA65.B.00355/19