DATASHEET



A-K8P-M12-S-G-10M-GY-1-X-A-4

- 10 m
- Pre-wired cable
- 8-pole

Data

Ordering data

Product type description	A-K8P-M12-S-G-10M-GY-1-X-A-4
Article number (order number)	103011413
EAN (European Article Number)	4030661477497
eCl@ss number, version 12.0	27-06-03-11
eCl@ss number, version 11.0	27-06-03-11
eCl@ss number, version 9.0	27-06-03-11
ETIM number, version 7.0	EC001855
ETIM number, version 6.0	EC001855

Approvals - Standards

Certificates	cULus

General data

Standards	EN IEC 61076-2-101
Gross weight	515 g

General data - Features

Halogen free	Yes (1)
Cable drag chain suitable	Yes (1)
Number of poles	8
Number of cable wires	8

Mechanical data

Tightening torque, maximum	1 Nm

Mechanical data - Connection technique

Length of cable	10 m
Wire cross-section	0.25 mm^2
Cable diameter	6.2 mm
Bending radius (fixed)	5 x Ø-cable
Bending radius (repeated)	10 x Ø-cable
Colour of the Cable mantle	Grey
Material of the Cable mantle	PVC

Mechanical data - connector side A

Connector typ	Female connector, M12
Design	straight
Connector coding	A
Connector latching	Screw locking
Material of the gland	Metal, CuZn, nickel-plated
Material of the handle	Plastic, TPU
Colour of the handle	Black

Ambient conditions

Degree of protection	IP65 IP67 IP69
Ambient temperature (Connector)	-30 ... +90 °C

Ambient temperature (fixed)	-25 ... +80 °C
Ambient temperature (moved)	+0 ... +80 °C

Electrical data

Thermal test current	2 A
Rated operating voltage	30 VAC
Rated operating voltage	30 VDC
Operating current	2,000 mA

Pin assignment

PIN 1	White
PIN 2	Brown
PIN 3	green
PIN 4	yellow
PIN 5	Grey
PIN 6	Pink
PIN 7	Blue
PIN 8	red

Ordering code

Product type description:
(1)-(2)-(3)-(4)-(5)-(6)-(7)-(8)-(9)-(10)-(11)-(12)-(13)-(14)

(1)

A	Pre-wired cable
AHT	Pre-wired cable high temperature
AIE	Pre-wired cable Industrial Ethernet
V	Interconnector
VIE	Interconnector Industrial Ethernet
S	Connector without cable

(2)a

K	female connector
KK	Female plug - female plug
S	Male connector
SS	Connector - connector
SK	Connector - female plug

(2)b

3P	3-pole
4P	4-pole
5P	5-pole
6P	6-pole
7P	7-pole
8P	8-pole
9P	9-pole
10P	10-pole
11P	11-pole
12P	12-pole
23P	23-pole
2P+PE	2 pole + PE
3P+PE	3 pole + PE

(3)

M8	M8 / round 8 mm
M12	M12
M18	M18
M23	M23
DIN43650	DIN 43650

(4)

R	Latching interlocking
S	Screw locking

(5)

G	straight

W	angled

(6)

X	without
0.3M	0,3 m
0,5M	0,5 m
1M	1 m
1.5 m	1.5 m
2M	2 m
2.5M	2.5 m
3M	3 m
5M	5 m
10M	10 m
15M	15 m
20M	20 m

(7)

X	without
BK	Black
GY	Grey
OG	Orange
WH	White

(8)

X	-
1	PVC
2	PUR
3	Rubber
4	Silicone
5	PTFE

(9)

X	Neutral
1LP	1x LED - PNP

2LP	2x LED - PNP
3LP	3x LED - PNP

(10)

X	without
A	A-coding
B	B-Coding

(11)

1	without
2	UL
3	CSA
4	USA/CAN

(12)

69	IP69K

(13)

VA	Material, thread/knurled nut, stainless steel (VA)

(14)

075	0.75 mm² cable section


Pictures

Product picture (catalogue individual photo)



ID: k1208f04
| 158.0 kB | .jpg | 352.778 x 235.303 mm - 1000 x 667 px - 72 dpi
| 19.5 kB | .png | 74.083 x 49.389 mm - 210 x 140 px - 72 dpi
| 22.4 kB | .jpg | 123.472 x 82.197 mm - 350 x 233 px - 72 dpi

Contact arrangement



ID: km23-k8a
| 18.0 kB | .cdr |
| 5.5 kB | .png | 73.731 x 79.728 mm - 209 x 226 px - 72 dpi
| 155.6 kB | .jpg | 352.778 x 380.647 mm - 1000 x 1079 px - 72 dpi

Schmersal India Pvt. Ltd., Plot No - G-7/1, Ranjangaon MIDC, Tal. - Shirur, Dist.- Pune 412 220
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on: 24/12/2024, 7:01 am