Specifications

Eaton 135995



Catalog Number: 135995

Eaton Moeller® series E57 Proximity switch, E57 Premium+ Series, 1 N/O, 2-wire, 20 - 250 V AC, M12 x 1 mm, Sn= 2 mm, Flush, Stainless steel, 2 m connection cable

General specifications

Product Name
Eaton Moeller® series E57 Proximity switch

Catalog Number
135995

EAN
4015081327881

Product Length/Depth
158.75 mm

Product Height
50.8 mm

Product Width
133.35 mm

Product Weight
0.103 kg

Certifications
CE
UL
CSA
CSA Class No.: 3211-03
CSA-C22.2 No. 14
UL File No.: E166051
IEC/EN 60947-5-2
UL 508
CSA File No.: 50513
UL Category Control No.: NRKH, NRKH7

Powering Business Worldwide

Product specifications

Type
Inductive sensor

Electric connection type
Cable

Enclosure material finishing
Other

Actuation type
Metallic Target

Enclosure material
Metal

Enclosure type
Cylinder, screw-thread

Category (EN 954-1)
B

Explosion safety category for dust
None

Explosion safety category for gas
None

Safety performance level (EN ISO 13849-1)
None

SIL (IEC 61508)
None

Ambient operating temperature - max
70 °C

Ambient operating temperature - min
-25 °C

Diameter sensor
12 mm

Number of contact energized outputs with signalling function
0

Number of contacts (normally open contacts)
1

Number of outputs (protected contact energized)
0

Number of outputs (protected semiconductor)

Resources

Brochures
eaton-sensors-brochure-br053001en-en-us.pdf

Catalogs
Product Range Catalog Sensors – products, basic information, applications

Declarations of conformity
DA-DC-00004651.pdf

DA-DC-00004656.pdf

Drawings
1360DRW-92

Installation instructions
IL05301003Z

Multimedia
We make what matters

0

Number of outputs (semiconductor with signaling function)

1

Operational current (Ib) in the switched state at 24 V DC

10 A

Output current at protected output - max

0 mA

Rated control supply voltage (Us) at AC, 50 Hz - max

250 V

Voltage type

AC

Mounting method

Flush mounting

Material

Stainless steel

Connection type

2-wire

2 m connection cable

Installation type

Concise

Degree of protection

IP67

NEMA 4X, 6, 13

Interface type

None

LED indicator

Status indication of Switching state: Red LED

Switch function type

Normally open contact

Load current

1 - 500 mA (Ie, at 25 °C)

1 - 250 mA (Ie, 70 °C)

Residual current

0.1 mA (through the load in the blocked state at 230 V AC and 24 V DC)

Shock resistance

30 g, Mechanical, Shock duration 11 ms

Switching frequency

20 Hz

Voltage rating - max

250 V

Width sensor

0 mm

Product category

E57 Premium+ Series

Switching output type

Two-wire

Temperature drift of sn

10 %

Rated control supply voltage (Us) at AC, 50 Hz - min

20 V

Rated control supply voltage (Us) at AC, 60 Hz - max

250 V

Rated control supply voltage (Us) at AC, 60 Hz - min

20 V

Rated control supply voltage (Us) at DC - max

0 V

Rated control supply voltage (Us) at DC - min

0 V

Rated switching distance (Sn) - max

2 mm

Repeatability

3 %

Sensor height

0 mm

Sensor length

62 mm

Supply voltage - max

250 V

Supply voltage - min

20 V

Switching hysteresis of Sn

20 %

Voltage drop (Ud)

2.5 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia