Comus Group of Companies

PRODUCT DATA SHEET

Manufactured in UK



Drawings not to scale
All dimensions in mm (inches) nominal

Different magnets will give varying operating distances.

SPECIFICATION

CONTACT FORM/STYLE		C/CHANGEOVER
SWITCHING VOLTAGE	Max. Vac	175
SWITCHING CURRENT	Max. A	0.25
SWITCHING CAPACITY (RESISTIVE)	Max. VA	3.0
CONTACT RESISTANCE	Max. mΩ	150
SWITCHING DISTANCE	Min. mm	3.0
OPERATING TEMPERATURE		
CONTINUOUS	Deg. ˚C	-20˚ + 85˚
INTERMITTENT	Deg. ˚C	-20˚ + 105˚
STORAGE TEMPERATURE	Deg. ˚C	-20° +90°
CASE MATERIAL		Polystyrene

This product is fully sealed to give maximum mechanical protection and minimise the ingress of dust and moisture. As a guide, the product is expected to meet the requirements of IP65.

PROXIMITY - Reed Switch - Cylindrical - Plastic

PART NUMBER

Rev. No.	Revision Note	Date	Signature
D	Web Site 2001	1-4-01	RG

As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and details of our full design and manufacturing service. All products are supplied to our standard conditions of sale otherwise agreed in writing.

©2001 Copyright Comus Group of Companies

The Comus Group of Companies consist of:
Assemtech Europe Limited
E. Bachem GmbH
Comus International
W. Gunther GmbH
Gunther Belgium
Gunther France
S.T.G.