# Flashguard LED Beacons

Flashguard weatherproof LED beacons are ideal visual indicators in a variety of applications.

All Flashguard beacons are fitted with a diffuser for greater visibility and spread of light. Two styles are available. Standard and Ultra Low Profile.

**Standard:** includes a terminal block and a 27mm deep base supplied with a seal and grommet.

**Ultra Low Profile:** comes complete with a screw and nylon wing nut and is supplied with mounting gasket and 40cm of cable.

A weatherproof cable connector is available to upgrade the product from IP65 rating to IP67.

## Features

- **Compact, ultra modern sleek appearance**
- **Long life LED design**
- **Ease of installation with first-fix option on standard models**
- **Weatherproof to IP67 (with cable connector)**
- **White, high quality polycarbonate housing**
- **Vandal-resistant safety locking mechanism**
- **Flashing or static indicators**

## Lens Colour Options






**Applications -** Fire alarm; security alert; emergency warning; process control alarm

Standard and Fire Style




Ultra Low Profile Style




## Specifications

| Type and Style | Part No. Red Lens | Part No. Amber Lens | Part No. Clear Lens | Part No. Blue Lens | Part No. Green Lens | Voltage | Current | Static or Flashing | Flash Rate |
|---|---|---|---|---|---|---|---|---|---|
| LED Standard | QBS-0007 | QBS-0008 | QBS-0009 | QBS-0010 | QBS-0011 | 110V AC | 32mA | Static | N/A |
| LED Standard | QBS-0012 | QBS-0013 | QBS-0014 | QBS-0015 | QBS-0016 | 110V AC | 32mA | Flashing | 1Hz |
| LED Standard | QBS-0022 | QBS-0023 | QBS-0024 | QBS-0025 | QBS-0026 | 230V AC | 32mA | Static | N/A |
| LED Standard | QBS-0027 | QBS-0028 | QBS-0029 | QBS-0030 | QBS-0031 | 230V AC | 32mA | Flashing | 1Hz |
| LED Standard | QBS-0060 | QBS-0063 | QBS-0065 | QBS-0067 | QBS-0069 | 11/35V DC | 50mA** | Static/Flashing* | 1Hz |
| LED Ultra Low Profile | QBS-0062 | QBS-0064 | QBS-0066 | QBS-0068 | QBS-0070 | 11/35V DC | 50mA** | Static/Flashing* | 1Hz |

*These units are user-configurable
**Clear, blue and green versions draw upto 100mA

**IP Rating:** IP65 (Standard) IP67 (With cable connector) **Operating Temp:** -20°C to +70°C **Construction:** UV Stabilised Polycarbonate
**Weight:** 0.14kg (Standard) 0.08kg (Ultra)

klaxon
Signalling Solutions