Your Expert Partner for **Human Machine Interfaces**

Pendant control

Distribution by
Rs-online

46-446.1418



https://www.rs-online.eao.com/component/46-44...

Your product:



46-446.1418
Pendant control

Loading . . .

FRONT

Colour:	Yellow

MOUNTING

Mounting cut-out:	Ø 22 mm
Mounting type:	Panel mounting

ELECTRICAL CHARACTERISTICS

Rated insulation voltage Ui:	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
Pollution degree:	3
Protection class:	II, according to EN / IEC 61140

MECHANICAL CHARACTERISTICS

Tightening torque:	0.8 ... 1.2 Nm (7.1÷10.6 Lb-in)
Weight:	0.2 kg

AMBIENT CONDITION

IP front protection:	IP65, IP66
IK front protection:	IK08
Operating temperature:	– 35 °C ... + 80 °C

CERTIFICATE

Approbations:	CSA, UL

Conformities:	CE
REACH:	REACH compliant
RoHS:	RoHS compliant
Standards:	CSA C22-2, IEC EN 60204-1, IEC EN 60947-1, IEC EN 60947-5-1, UL508

OTHER

Short Description:	Pendant control
Number of holes:	2
Dimension:	83 mm x 137 mm
Housing material:	Plastic
Product attributes:	Suitable for outdoor applications

Dimension drawings:

