DATASHEET - SL4-L120-Y

Continuous light module; yellow; LED;120 V

Part no.	**SL4-L120-Y**
	171323
EL Number (Norway)	**4137558**

Product name	Eaton Moeller® series SL4 Continuous light module
Part no.	SL4-L120-Y
EAN	4015081678624
Product Length/Depth	43 millimetre
Product height	75 millimetre
Product width	43 millimetre
Product weight	0.043 kilogram
Certifications	CSA-C22.2 No. 94-91 UL 508 UL report applies to both US and Canada Certified by UL for use in Canada UL IEC/EN 60947-5-1 UL Category Control No.: NKCR IEC/EN 60529 CSA-C22.2 No. 14-10 UL File No.: E29184 CE CSA Class No.: NKCR7
Product Tradename	SL4
Product Type	Continuous light module
Product Sub Type	None
Color	Yellow
Enclosure color	Black
Functions	Continuous light
Light modules	LED
Number of modules	Max. 5 (with standard base) Max. 10 (with base for mounting on both sides)
Connection to SmartWire-DT	No
Current consumption	0.03 A, at 110/120 V AC
Degree of protection	NEMA 4X IP66
Lifespan, electrical	100,000 h
Light type	Continuous light
Material	Enclosure: Polycarbonate (PC) Cap: Polycarbonate (PC)
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Product Category	SL signal towers
Radiation angle	360 °
Rated impulse withstand voltage (Uimp)	4000 V AC
Shock resistance	15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
Type	Continuous light module
Voltage type	AC
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	60 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Leakage current			0.003 A
Rated insulation voltage (Ui)			250 V
Rated operational voltage (Ue) at AC - min			110 V
Rated operational voltage (Ue) at AC - max			120 V
Rated operational voltage (Ue) at DC - min			0 V
Rated operational voltage (Ue) at DC - max			0 V

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Optical module for signal tower (EC000232)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Optical module for signal tower (ecl@ss10.0.1-27-37-12-20 [AKF038014])

Function			Continuous light
Colour			Yellow
Outer diameter		mm	43
Operating voltage at AC 50 Hz		V	110 - 120
Operating voltage at AC 60 Hz		V	110 - 120
Operating voltage at DC		V	0 - 0
Voltage type			AC
Lamp type			LED
Colour housing			Black
Degree of protection (IP)			IP66
Degree of protection (NEMA)			4X

© 04/2023 by Eaton Industries GmbH