


Acoustic device 24V, continuous or pulsed tone

Part no. SL4-AP24
Article no. 171379

Catalog No. SL4-AP24

Delivery programme

Product range			SL4 signal towers
Basic function			Acoustic module
Protection type			IP66
Rated operational voltage	U_e	V	24 V AC/DC
Rated operational current	I_e	mA	39
Description			Continuous tone or pulsed tone, adjustable with internal dip switches. Sound pressure 80 dB. f = 4000 Hz Place only at the highest position on a pole
Colour			
			
Function			
			
Connection to SmartWire-DT			no

Approvals

Product Standards	IEC/EN 60947-5-1; UL 508; CSA-C22.2 No. 14-10; CSA-C22.2 No. 94-91; CE marking
UL File No.	E29184
UL Category Control No.	NKCR
CSA File No.	UL report applies to both US and Canada
CSA Class No.	NKCR7
North America Certification	UL listed, certified by UL for use in Canada
Degree of Protection	UL Type 4, 4X, 13

General



Standards			IEC/EN 60947-5-1
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60069-2-30
Mounting position			As required
Mechanical shock resistance		g	> 15 according to IEC 60068-2-27 Shock duration 11 ms Sinusoidal
IEC degree of protection			IP66 IEC/EN 60529
Protection type UL			Type 4, 4X, 13
Material			Enclosure: Polycarbonate (PC), black Cap: Polycarbonate (PC)
Ambient temperature		°C	-30 - +60
Weight		g	43

Contacts

Rated impulse withstand voltage	U_{imp}	V AC	4000
Rated insulation voltage	U_i	V	250
Overvoltage category/pollution degree			III/3

modules

Leakage current		A	< 0.003

Type of tone			Continuous or pulsed tone
Types of sound			2 versions, table of sound types
Sound setting			Internal; 1 pole DIP
Table of sound types			**Table of sound types** **Sound type** / **DIP switch settings** / **Frequency** / **Diagram** / **Repeat rate** / **Special application** / **Max. volume** **SL4-AP…** / Continuous tone / approx. 4000 Hz /  / - / - / 80 dB Pulsed tone / approx. 4000 Hz /  / approx. 2 Hz / - / 80
Sound pressure		dB	80
Transmission angle			360°
Current-/power consumption			
24 V AC/DC		A	0.039
Voltage levels			24 V AC/DC ± 10 %


Technical data ETIM 5.0

Low-voltage industrial components (EG000017) / Acoustic module for signal tower (EC001261)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Signal column element, acoustic (ecl@ss8-27-37-12-37 [AKF055010])

Function			Continuous tone/pulse tone
Outer diameter		mm	43
Degree of protection (IP)			IP66
Colour			Black
Operating voltage at AC 50 Hz		V	24 - 24
Operating voltage at AC 60 Hz		V	24 - 24
Operating voltage at DC		V	24 - 24
Voltage type			AC/DC
Tone adjustable			Yes

Dimensions



Additional product information (links)

IL047001ZU SL4 Main Instruction	
IL047001ZU SL4 Main Instruction	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL047001ZU2013_02.pdf
IL047001ZU SL4, instructions générales	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL047001ZU2013_02.pdf

© 07/2014 by Eaton Industries GmbH