Specifications

Eaton 100673

Catalog Number: 100673

Eaton Moeller series NZM - Molded Case Circuit Breaker. Door coupling rotary handle, red-yellow max 60mmshaft, size 3



General specifications

Product Name
Eaton Moeller series NZM operating element NA

Catalog Number
100673

EAN
4015081005734

Product Length/Depth
100 mm

Product Height
230 mm

Product Width
120 mm

Product Weight
1.47 kg

Compliances
UL/CSA
IEC
RoHS conform

Certifications
UL (File No. E140305)
CE marking
IEC60947
UL489
CSA (File No. 22086)
CSA certified
UL listed
UL (Category Control Number DIHS)
CSA (Class No. 1437-01)
CSA-C22.2 No. 5-09

Powering Business Worldwide

Product specifications

Used with

NZM3, N(S)3

Type

Accessory Door coupling rotary handle

Special features

Complete including rotary drive and coupling parts Extension shaft additionally required. Cannot be combined with mechanical interlock For maximum shaft length 60 mm Without shaft support Cannot be combined with NZM...-XDZ additional handle External warning plate/designation label can be clipped on. Door coupling rotary handle for operating the switch through a closed control panel door

Features

Red-yellow for emergency switching off
Lockable

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Resources

Brochures

eaton-digital-nzm-brochure-br013003en-en-us.pdf

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM3

Drawings

eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-006.eps

eaton-circuit-breaker-door-nzm-rotary-handle-dimensions-003.eps

eaton-circuit-breaker-padlock-nzm-rotary-handle-dimensions.eps

eaton-circuit-breaker-door-nzm-rotary-handle-3d-drawing-004.eps

Installation instructions

IL01208007Z

Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

mCAD model

DA-CD-nzm3_xtvd_60

DA-CS-nzm3_xtvd_60

Technical data sheets

eaton-nzm-technical-information-sheet

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Color

Black

Fitted with:

Padlock

Frame

NZM3

Suitable for

Emergency stop

Power circuit breaker

Switch disconnector

Cover/door type

Door opens only with active rotation beyond the 0 position

Door interlock not defeated in the locked OFF position.

Lock number

Single lockable

Locking facility

With door interlock

Lockable on the handle on the switch using up to 3 padlocks

Degree of protection / NEMA enclosure type

IP66

4X. 12

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia