Order code : 66242396

Type code : 63V.50-E-MAERZZ-ND-UZZ ZZZ-ZZZZZ TA3BI1ZZ2DCAZ11MF

63V.50.100 0 mbar...100 mbar 1/2 NPT lower mount

Capsule pressure gauge, process industry series

Permissible ambient temperature: Standard

case with blow-out disc back

Case material: Stainless steel

class 1.6

IP 65

Case filling fluid: prepared for filling

Single packing

*EN 837-3* *WIKA*

*Cl.1.6*

Serial number *...*

Capsule pressure gauge, process industry series

Model: 63V.50

Specifications according to data sheet: PM 06.03

Measuring system: stainless steel

Case: stainless steel

Bezel ring: cam ring (bayonet type), stainless steel

Movement: stainless steel

Case filling: suitable for filling

Nominal size: 100 mm

Unit: mbar

Scale range: 0 mbar...100 mbar

Process connection: 1/2 NPT

Connector location: lower mount

Case type: case with blow-out disc back

Accuracy class: class 1.6

Movement: stainless steel

Ingress protection: IP 65

Case filling fluid: prepared for filling

Package: Single packing

Case surface: bare

Pointer: standard pointer

Pointer colour: black

Permissible ambient temperature: Standard

Permissible medium temperature: Standard

Case material: Stainless steel

Dial description:

Pressure Gauge Standard: International (standard Europe)

color for 1.scale (outside): black

dial background: White

Manufacturer logo: *WIKA*

Serial number *...*

norm-mark on dial: *EN 837-3*

accuracy class on dial: *Cl.1.6*

inner packages label: Standard (with Wika Logo)

outside packages label: Standard (with Wika Logo)