PRODUCT-DETAILS

ZLS905E58-3L

Starter pack



General Information

Extended Product Type	ZLS905E58-3L
Product ID	2CCA183138R0001
EAN	7612271413712
Catalog Description	Starter pack
Long Description	Starter pack Touch proof with 58 Modules L1,L2,L3 Pluggable socket system SMISSLINE TP is completely fingersafe (IP2XB) together with the socket end piece

Technical

Standards	IEC/EN 61439-6
Rated Operational Voltage	690 / 1000 V AC/DC
Rated Current (I_n)	125 A
Model Number	Flat
Surface Finishing	Tinned
Options Provided	3L

© 2024 ABB. All rights reserved.

Material Compliance

RoHS Information	9AKK107991A9646
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20170426
REACH Declaration	9AKK108467A9561
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20230417
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Environmental Information	9AKK108467A9561

Dimensions

Product Net Width	111 mm
Product Net Height	1058 mm
Product Net Depth / Length	34 mm
Product Net Weight	1778 g
Dimension Diagram	9AKK107492A6192

Ordering

Package Level 1 Units	carton 1 piece
Package Level 1 Gross Weight	1918 g
E-Number (Switzerland)	809992790

Certificates and Declarations

Declaration of Conformity - CE	9AKK107991A9646

Installation

Instructions and Manuals	9AKK107680A2315

Popular Downloads

Data Sheet, Technical Information	9AKK107492A6192

Classifications

ETIM 8	EC001522 - Busbar
ETIM 9	EC001522 - Busbar


© 2024 ABB. All rights reserved.

Subject to change without notice

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85389030
eClass	V11.0 : 27370303
Object Classification Code	W

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems → Plug-in Distribution Systems Accessories → Accessories for Plug-in Distribution Systems 125A



© 2024 ABB. All rights reserved.