Specifications

Eaton 195322

Catalog Number: 195322

Eaton xEnergy Basic LV systems Low voltage switchgear. Surface-mounted installation distributor IP55, EP WxHxD=850x1160x270mm, gray, swivel lever



General specifications

Product Name	Catalog Number
Eaton xEnergy Basic empty enclosure	195322
EAN	Product Length/Depth
9010238091962	270 mm
Product Height	Product Width
1160 mm	850 mm
Product Weight	Compliances
40.3 kg	RoHS conform

Powering Business Worldwide

Product specifications

Type

Basic device

Features

Connectable

Mounting plate depth-adjustable

EMC-version

Fitted with:

Door

Surface finishing

Powder coating

Degree of protection

IK10

IP55

Other

Material quality

Other

Color

Gray

Permissible load of the mounting plate according to IEC 62208 - max

0 N

Number of locks

0

RAL-number

7035

Material

Steel

Mounting method

Wall fastening

Functions

Basic device

Installation type

Floor standing wall model

Number of covers/doors

1

Suitable for

Metrical mounting

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Drawings

eaton-low-voltage-switch-gear-dimensions-1230dim-437.eps

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Permissible load of the enclosure according to IEC 62208 - max

0 N

Permissible load of the door(s) according to IEC 62208 - max

0 N

Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890

0 W

Number of connector holes

0

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia