


Model Number


V31-WM-5M-PUR

4-pin, M8 socket, PUR cable

Features

- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Gold-plated and machined contacts
- Resistant to microbes and hydrolysis
- Halogen-free


Dimensions



Technical data

General specifications		
Number of pins		4
Connection 1		female connector
Construction type 1		right angle
Threading 1		M8
Connection 2		cable end
Electrical specifications		
Operating voltage	U_B	max. 30 V AC/DC
Test voltage		> 1500 V_{eff} AC
Operating current		max. 3 A
Volume resistance		< 5 mΩ
Ambient conditions		
Ambient temperature		-40 ... 90 °C (-40 ... 194 °F) cable, fixed: -40 ... 80 °C (-40 ... 176 °F) cable, flexing: -20 ... 80 °C (-4 ... 176 °F)
Pollution Degree		3
Mechanical specifications		
Contact elements		spring-loaded contact socket
Pin diameter		1 mm
Protection degree		IP67
Material		
Contacts		CuSn / Au
Contact surface		Au
Body		TPU, green
Cable		PUR
Slotted nut		Diecast zinc
Core insolation		PP
Cable		fine-strand, flexible
Sheath diameter		Ø 4.3 mm
Bending radius		> 15 x cable diameter, induced > 8 x cable diameter, fixed
Color		grey
Cores		4 x 0.25 mm^2
Conductor construction		14 x 0.15 mm Ø
Length	L	5 m
Flammability		
Contact material		94 HB
Housing		94 V-2

Electrical connection



Release date: 2012-01-19 14:18 Date of issue: 2012-01-19 035491_eng.xml

Subject to modifications without notice
Copyright Pepperl+Fuchs