Specifications

Eaton 6093346

Catalog Number: 6093346

Eaton DMM Switch-disconnector, DMM, 160 A, 4 pole, With black rotary handle and drive shaft



General specifications

Product Name
Eaton DMM Switch-disconnector

Catalog Number
6093346

EAN
8711426741881

Product Length/Depth
155 mm

Product Height
115 mm

Product Width
137 mm

Product Weight
0.975 kg

Certifications
Lloyds
CE
RoHS
IEC/EN 60947-3
EAC
IEC/EN 60204
IEC/EN 60947
KEMA
VDE 0660

Powering Business Worldwide

Product specifications

Product Category

Main switch

Switch-disconnector

Features

Version as maintenance-/service switch

Version as main switch

Actuator color

Black

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be

Resources

Catalogs

Product Range Catalog Industrial switch-disconnectors

Eaton-industrial-switch-disconnectors-catalogue-ca008011en-en-gb.pdf

Declarations of conformity

DA-DC-00004933.pdf

DA-DC-00004903.pdf

eCAD model

DA-CE-ETN.DMM-160_4

Installation instructions

IL008025ZU

Wiring diagrams

eaton-rotary-switches-dmm-switch-disconnector-wiring-diagram.eps

eaton-rotary-switches-switch-dmm-switch-disconnector-wiring-diagram.eps

evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Fitted with:

Black rotary handle and drive shaft

Pollution degree

3

Rated impulse withstand voltage (Uimp)

6000 V

Rated permanent current at AC-21, 400 V

160 A

Rated permanent current at AC-23, 400 V

140 A

Rated uninterrupted current (Iu)

160 A

Static heat dissipation, non-current-dependent Pvs

0 W

Stripping length (main cable)

21 mm

Switching power at 400 V

0 kW

Accessories

Auxiliary contact fitted by user.
Connection materials included with supplied equipment.

Device construction

Built-in device fixed built-in technique

Rated short-time withstand current (Icw)

2,5 kA, Contacts, 1 second
2.5 kA

Electrical connection type of main circuit

Screw connection

Mounting position

As required

Actuator type

Short thumb-grip

Ambient operating temperature - max

55 °C

Ambient operating temperature - min

-25 °C

Ambient storage temperature - max

80 °C

Ambient storage temperature - min

-30 °C

Equipment heat dissipation, current-dependent Pvid

8 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

7.4 W

Number of auxiliary contacts (change-over contacts)

0

Number of auxiliary contacts (normally closed contacts)

0

Rated conditional short-circuit current (Iq)

30 kA at 415 V

50 kA

Overvoltage category

III

Breaking current

13.7 kA

Degree of protection (front side)

IP20

Number of poles

Four-pole

Mounting method

Surface mounting

Degree of protection

NEMA Other

Suitable for

Intermediate mounting

Ground mounting

Distribution board installation

Number of switches

1

Lifespan, mechanical

10,000 Operations

Let-through energy

Max. 134 kA²s

Terminal capacity

6 - 70 mm², flexible with ferrules to DIN 46228

Safety parameter (EN ISO 13849-1)

B10d values as per EN ISO 13849-1, table C.1

Number of auxiliary contacts (normally open contacts)

0

Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3)

10000 A

Rated breaking capacity at 500 V (cos phi to IEC 60947-3)

528 A

Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3)

336 A

Rated insulation voltage (Ui)

1000 V

Rated operating voltage (Ue) - max

690 V

Rated operating voltage (Ue) - min

690 V

Rated operational voltage (Ue) at AC - max

690 V

Rated operational current (Ie) at AC-21, 400 V, 415 V

160 A

Short-circuit protection rating

125, Fuse, Contacts

Rated operational current (Ie) at AC-21, 500 V

160 A

Rated operational current (Ie) at AC-21, 690 V

160 A

Rated operational current (Ie) at AC-22, 380 V, 400 V, 415 V

160 A

Rated operational current (Ie) at AC-22, 500 V

160 A

Rated operational current (Ie) at AC-22, 690 V

160 A

Rated operational current (Ie) at AC-23A, 400 V, 415 V

160 A

Rated operational current (Ie) at AC-23A, 500 V

66 A

Rated operational current (Ie) at AC-23A, 690 V

42 A

Rated operational current for specified heat dissipation (In)

160 A

Rated operational power at AC-23A, 400 V, 50 Hz

75 kW

Rated operational power at AC-23A, 500 V, 50 Hz

45 kW

Rated operational power at AC-23A, 690 V, 50 Hz

37 kW

Rated operational power at AC-3, 380/400 V, 50 Hz

0 kW

Tightening torque

7 Nm, Screw terminals

Uninterrupted current

Rated uninterrupted current Iu is specified for max. cross-section.

Width in number of modular spacings

6

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia