Date: 12/04/2023

RLS-1000; Guide tube length: 175.0; 2 switching outputs

RLS-1000; Guide tube length: 175.0; 2 switching outputs

Item number: 14219777

Quantity: 1 pcs.

Order code: RLS-10004M200550201300ZZZZZZZZZZZZ1DN8S017504Z1
Z1W101ARS1ZL4

Overview:
RLS-1000; Guide tube length: 175.0; 2 switching outputs
Magnetic float switch, Stainless steel version Model RLS-1000
Output Signal: 2 switching outputs
max. switching power: n.o./n.c.: AC 230 V; 100 VA; 1 A / DC 230 V; 50 W; 0,5 A
max. switching power: Changeover/SPDT: AC 230 V; 40 VA; 1 A / DC 230 V; 20 W; 0,5 A
Unit of measure switching position: mm
Switching function - Switch output 1 : Normally open / n.o.
Switch position - Switch output 1 : 55.0
Switching function - Switch output 2 : Normally open / n.o.
Switch position - Switch output 2: 130.0
Electrical connection: Cable outlet PVC, IP67
Cable length: 5 m / 16.4 ft
pin assignment el. connection: see product label
Process connection: G 1/2, installation from inside
Guide tube length: 175.0 mm
medium temperature: -30 °C ... 80 °C
Wetted parts: Stainless steel 1.4571
Float: Cylindrical float Ø 44 mm, 1.4571, PN16
Specifications according to data sheet: LM 50.03

Details:
RLS-1000; Guide tube length: 175.0; 2 switching outputs
Magnetic float switch, Stainless steel version Model RLS-1000
Output Signal: 2 switching outputs
max. switching power: n.o./n.c.: AC 230 V; 100 VA; 1 A / DC 230 V; 50 W; 0,5 A
max. switching power: Changeover/SPDT: AC 230 V; 40 VA; 1 A / DC 230 V; 20 W; 0,5 A
Unit of measure switching position: mm
Switching function - Switch output 1 : Normally open / n.o.
Switch position - Switch output 1 : 55.0
Switching function - Switch output 2 : Normally open / n.o.
Switch position - Switch output 2: 130.0
Electrical connection: Cable outlet PVC, IP67
Cable length: 5 m / 16.4 ft
pin assignment el. connection: see product label
Process connection: G 1/2, installation from inside
Guide tube length: 175.0 mm
medium temperature: -30 °C ... 80 °C

© 2023 - WIKA Instruments s.a.r.l.

Wetted parts: Stainless steel 1.4571
Float: Cylindrical float Ø 44 mm, 1.4571, PN16
Specifications according to data sheet: LM 50.03

© 2023 - WIKA Instruments s.a.r.l.