PRODUCT-DETAILS

XLP1

XLP1 Fuse Switch Disconnector



General Information

Extended Product Type	XLP1
Product ID	1SEP101891R0001
EAN	7025840013723
Catalog Description	XLP1 Fuse Switch Disconnector
Long Description	XLP1,3-pole,250A, without clamps or bolts

ABB EcoSolutions

ABB EcoSolutions	Yes
Circular Design Principles Recyclability Rate	Design for Closing Resource Loops - Standard EN45555 - 94.1 %
End of Life Instructions	9AKK108469A3432
Environmental Product Declaration - EPD	9AKK108468A2201 9AKK108468A2281
Group Waste to Landfill Target	No non-hazardous waste is sent to a landfill UL 2799 Zero Waste To Landfill Validation available

© 2024 ABB. All rights reserved.

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Popular Downloads

Data Sheet, Technical Information	1SEC312012D0201
Instructions and Manuals	No Instructions and Manuals needed
Environmental Product Declaration - EPD	9AKK108468A2201 9AKK108468A2281
End of Life Instructions	9AKK108469A3432

Environmental

Degree of Protection	IP30

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85389099
Country of Origin	Bulgaria (BG) China (CN)

Dimensions

Product Net Width	185 mm
Product Net Height	270 mm
Product Net Depth / Length	116 mm
Product Net Weight	1.6 kg

Container Information

Package Level 1 Units	shrink-wrap 1 piece
Package Level 1 Width	185 mm
Package Level 1 Depth / Length	116 mm
Package Level 1 Height	270 mm
Package Level 1 Gross Weight	1.6 kg
Package Level 1 EAN	7025840013723
Package Level 2 EAN	7025840013723

Technical

Degree of Protection	IP30

© 2024 ABB. All rights reserved.

Device Type Manager (DTM)	Fuseswitchdisconnector
Electronic Fuse Monitoring	No
Fuse Size	NH1
Fuse System	DIN
Handle Type	Front cover 3P
Mounting Type	Baseplate
Number of Poles	3P
Power Loss	at Rated Load 7.5 W
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 50 kiloampere rms
Rated Current (I_n)	250 A
Rated Frequency (f)	Main Circuit 50/60 Hz
Rated Impulse Withstand Voltage (U_{imp})	Main Circuit 8 kV
Rated Operational Current AC-21B (I_e)	(690 V) 200 A
Rated Operational Current AC-22B (I_e)	(500 V) 250 A (800 V) 250 A
Rated Operational Voltage	500 V AC 690 V AC 800 V AC
Rated Voltage (U_r)	500 V AC 690 V AC 800 V AC
Special Functions	Not Included
Standards	IEC60947-3 GB/T14048.3
Terminal Type	Lug terminals

Certificates and Declarations

Declaration of Conformity - CE	1SEP500050P0001

Classifications

Object Classification Code	S
ETIM 8	EC001040 - Fuse switch disconnector
ETIM 9	EC001040 - Fuse switch disconnector
eClass	V11.1 : 27371401
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601050
E-Number (Sweden)	2307320

© 2024 ABB. All rights reserved.

Categories

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → EasyLine



© 2024 ABB. All rights reserved.