Specifications

Eaton 116270

Catalog Number: 116270

Eaton xEnergy Basic LV systems Low voltage switchgear. Cable interconnect frame, HxWxD=200x400x300mm



General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic base element	116270
EAN	**Product Length/Depth**
4015081160099	291.5 mm
Product Height	**Product Width**
205 mm	405 mm
Product Weight	**Compliances**
6.21 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

Accessory
Accessory consideration
Floor-standing enclosure
Service distribution board IVS

Special features

For total weight >; 300 kg
Cladding removable on all sides
Can be fitted to top or bottom of the enclosure
Supplied assembled
Including fixing sundries
Cable clamp rail not included as standard

Type

Additional equipment for floor-standing service distribution board IVS

Accessory/spare part type

Cable marshalling box

Surface finishing

With powder coating

Color

Gray

Degree of protection

IP30

Unit type

Modular system

Load capacity - max

350 kg

RAL-number

7035

Suitable for enclosure building length/depth

300 mm

Suitable for enclosure building width

400 mm

Suitable for length/depth

300 mm

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Suitable for width

400 mm

Material

Sheet steel

Steel

Housing material

Sheet steel

Model

Base complete

Mounting method

Floor standing distribution board

Suitable for

Cable patch

Functions

Additional equipment

Impact strength

Other

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia