Description:

- RTD 100 Ω probe, class A, in compliance with NF EN 60751
  available in: 1 x 3 wires (simple) and 2 x 3 wires (duplex)
- 316L stainless steel protective sheathing
  available in: L1 length and Ø
- Cable length: 2 m
  available in: PVC, silicone and FEP





Models and codes for ordering

Probe Qty	Wiring	L1 (mm)	Ø (mm)	S1 PVC cable	S11 Silicon cable	S12 FEP cable
1 x 100 Ω	1 x 3 wires	50	1.6	L330111-503		
		100		L330111-506		
		150		L330111-507		
		250		L330111-509		
		50	3	L330112-503	L331112-503	L331212-503
		100		L330112-506	L331112-506	L331212-506
		150		L330112-507	L331112-507	L331212-507
		200		L330112-508	L331112-508	L331212-508
		100	4.5	L330113-506	L331113-506	L331213-506
		200		L330113-508	L331113-508	L331213-508
		300		L330113-510	L331113-510	L331213-510
		500		L330113-514	L331113-514	L331213-514
		50	6	L330114-503	L331114-503	L331214-503
		100		L330114-506	L331114-506	L331214-506
		150		L330114-507	L331114-507	L331214-507
		200		L330114-508	L331114-508	L331214-508
		300		L330114-510	L331114-510	L331214-510
		500		L330114-514	L331114-514	L331214-514
2 x 100 Ω	2 x 3 wires	200	6	L330144-508		L331244-508
		300		L330144-510		L331244-510
		500		L330144-514		L331244-514





Connection accessories: adjustable compression fitting

- Stainless steel body and ferrule
- Pressure resistance: see p. 7

Threading	Sheath Ø	Code
1/4" NPT	3 mm	L078830-000
1/4" NPT	4.5 mm	L078833-000
1/4" NPT	6 mm	L078836-000
1/2" NPT	6 mm	L078938-000

Other types of connection: see connection components



Electrical connection accessories:

- Standard three-pin connector

Code
L018290-000

Other types of electrical connection: see electrical connection