WXSB 200 Soldering Bath

Rework and preparation tool for tinning of component leads and removal of protective coatings.

WX compatible

Code-Number: T005 27 043 99

Health and safety
24 V low voltage operation and class 3 protection.

New powerful 200 W !

WXSB 200
The high power of the soldering bath ensures a quick warm up time and an even temperature throughout the bath.



ESD Safe
Will not damage or degrade sensitive components and is safe for use in protected assembly areas.

Wide temperature range!
Temperature variabel 100°C - 500°C.

Process Control
WX technology provides convenient and precise handling of the solder process and guarantees the end result.

Technical Data:	
Dimensions housing L x B x H	150 x 120 x 65 mm (5,90 x 4,72 x 2,55 inch)
Dimensions soldering bath L x B x H	58 x 33 x 19 mm (2,30 x 1,29 x 0,75 inch)
Voltage	24 V
Power Consumption	200 W
Heat-up time	approx. 10 min. 50°C - 350°C (122°F - 662°F)
Temperatur range	100°C - 500°C (212°F - 932°F)

Weller Tools GmbH
Carl-Benz-Straße 2
74354 Besigheim
Germany

Phone: +49 (0) 7143 / 580-0
Fax.: +49 (0) 7143 / 580-108
Email: info@weller-tools.com
Web: www.weller-tools.com