PRODUCT-DETAILS

CCL5-11

CCL5-11 Auxiliary Contact Block



General Information

Extended Product Type	CCL5-11
Product ID	1SBN011421R1008
EAN	3471522199133
Catalog Description	CCL5-11 Auxiliary Contact Block
Long Description	CCL5-11 is a 2-pole side mounted auxiliary contact block equipped with screw terminals and can be fitted on A9…16 contactors and N 4-pole contactor relays. CCL5-11 is available with one N.O. leading contact and one N.C. lagging contact for standard industrial environments.

Ordering

Minimum Order Quantity	2 piece
Customs Tariff Number	85389099

Popular Downloads

Data Sheet, Technical Information	1SBC100122C0202_Ch04

© 2024 ABB. All rights reserved.

Instructions and Manuals	FPTC407744P0001

Dimensions

Product Net Width	12 mm
Product Net Depth / Length	60 mm
Product Net Height	74 mm
Product Net Weight	0.05 kg

Technical

Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Rated Operational Voltage	Auxiliary Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz
Rated Operational Current AC-15 (I_e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 0.1 s 140 A for 1 s 100 A
Maximum Electrical Switching Frequency	1200 cycles per hour
Rated Operational Current DC-13 (I_e)	(24 V) 6 / 144 A (48 V) 2.8 / 134 A (72 V) 1 / 72 A (125 V) 0.55 / 69 A (250 V) 0.3 / 75 W
Rated Insulation Voltage (U_i)	acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
Terminal Type	Screw Terminals
Suitable For	A9 A12 A16 N22E N31E N40E

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

© 2024 ABB. All rights reserved.

WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CSA Certificate	CSA_1033838
Declaration of Conformity - CE	1SBD250809U1000
Declaration of Conformity - UKCA	1SBD250826U1000
EAC Certificate	EAC_RU C-FR ME77 B03391
GOST Certificate	GOST_POCCFRME77B07175
RINA Certificate	RINA_ELE172319XG001
UL Certificate	UL_071301E48139

Container Information

Package Level 1 Units	2 piece
Package Level 1 Width	100 mm
Package Level 1 Depth / Length	105.5 mm
Package Level 1 Height	35 mm
Package Level 1 Gross Weight	0.1 kg
Package Level 1 EAN	3471522199133
Package Level 2 Units	box 240 piece
Package Level 2 Width	300 mm
Package Level 2 Depth / Length	245 mm
Package Level 2 Height	308 mm
Package Level 2 Gross Weight	12 kg
Package Level 3 Units	2880 piece

Classifications

Object Classification Code	K
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
ETIM 9	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39121522
IDEA Granular Category Code (IGCC)	4743 >> Auxiliary contact block

© 2024 ABB. All rights reserved.

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors



© 2024 ABB. All rights reserved.