Specification
VT7
Single pole voltage indicator



The VT7 is a single pole contact voltage indicator which detects AC voltages of 50V-600V with bright LED indication.

The VT7 also has a self test function and is suitable for indoor and outdoor use.

It is ergonomically designed and of durable construction for both industrial and domestic applications.

- 50V-600V AC Self test function
- Bright LED indication
- Audible indication
- Overvoltage category
- CAT IV 300V, CAT III 600V

Electrical
Audible and visual indication
Voltage range: 50V - 600V AC rms
Frequency range: 50 - 60Hz
Test current: <5µA

Environmental
Temperature (Operating & Storage): -10°C to 55°C
Humidity (Operating & Storage): ≤ 85% R.H.
Altitude: up to 2000m

General
Power: 9V, PP3 alkaline battery (IEC 6LR61, NEDA 1604A)
Current consumption: 34mA max

Dimensions: 236(L) x 44(W) x 33(D) mm
Weight: 120g (battery included) approx
Includes: 9V PP3 battery, instructions

Safety
Conforms to BS EN61010-1 CAT IV 300V, CAT III 600V
Class II, Double Insulation
Pollution Degree: 2
IP rating: IP54
Water resistant

EMC
Conforms to BS EN61326-1

Due to policy of continuous development, Martindale Electric reserves the right to alter equipment specification and description outlined in this document without prior notice. No part of this document shall be deemed to be part of any contract for the equipment unless specifically referred to as an inclusion within such contract. © Martindale Electric Co. Ltd. 2013

Martindale Electric Company Ltd.
Metrohm House, Penfold Trading Estate, Imperial Way, Watford, WD24 4YY. Tel: 01923 441717 Fax: 01923 446900
sales@martindale-electric.co.uk www.martindale-electric.co.uk