Specifications

Eaton 35NHG02B-400

Catalog Number: 35NHG02B-400

Fuse-link, LV, 35 A, AC 400 V, NH02, gL/gG, IEC, dual indicator, live gripping lugs

General specifications

Product Name
Eaton Bussmann series low voltage NH Fuse

Catalog Number
35NHG02B-400

EAN
5027590477956

Product Length/Depth
150 mm

Product Height
63 mm

Product Width
40 mm

Product Weight
427 g

Compliances
RoHS Compliant
CE Marked

Certifications
IEC 60269-1
IEC 60269-2
DIN 43620

Product specifications

Type

Fuse

Application

industrial

Utilities, Solar, Wind

Amperage Rating

35 A

Fitted with:

Metal gripping lugs

Fuse size

NH02

Current type

AC

Breaking capacity

120 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Rated switching capacity

120 kA

Rated voltage AC

400 V

Class

Class gG/gL

Fuse type

Square body with knife blade contact

Utilization category

gL/gG (cable protection/equipment protection)

Interrupt rating

120 kAIC

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Resources

Catalogs

NH Fuse links, bases and gear

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

Declarations of conformity

UKCA NH Size 02/2, 400V fuse-links

CE NH Size 02/2, 400V fuse-links

Multimedia

Eaton Bussmann – NH fuse link portfolio

Presentations

NH Overview Video

Technical data sheets

720099 NH 400 Volts gG

Technical service bulletins

Datasheet - 35NHG02B-400

Watt losses

4.4 W

Connection

Blade end

Construction

NH02

Construction size

NH02

Fuse shape

Knife blade contacts

Square body

Voltage type

AC

Suitable for

Microswitch BVL50

Material

Ceramic body

Quantity

3

Voltage rating

400 V

Rated switching capacity AC

120 kA

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia