*Date: 11/04/2023*

# DCCH2A - 0...2,5 bar - Adaptor G 1/2 A-M - Adaptor M20x1,5-F

## Compact differential pressure switch

| | |
|---|---|
| Item number: | 48800220 |
| Quantity: | 1 pcs. |
| Order code: | DCCH2A-BBG B-4IMZZZACZZZ ZCA |
| Overview: | DCCH2A - 0...2,5 bar - Adaptor G 1/2 A-M - Adaptor M20x1,5-F<br>Compact differential pressure switch DC<br>static and one-side pressure: 25 bar<br>switch enclosure: aluminium,copper-free<br>contact version: 1xSPDT, silver contact<br>setting range: 0...2,5 bar<br>Set point definition: Set Point not defined<br>Process connection: Adaptor G 1/2 A-M<br>Electrical connection: Adaptor M20x1,5-F<br>Mounting: Enclosure with plate for wall or direct mounting<br>Diaphragm Material: Inconel 718<br>Brand: WIKA Instruments Italia<br>Specifications according to data sheet: PV 35.40<br>Repeatability of set point: ≤ 1% of span<br>Connection: Aluminium alloy |
| Details: | Compact differential pressure switch<br>Model DC<br>Specifications according to data sheet: PV 35.40<br>Repeatability of set point: ≤ 1% of span<br>static and one-side pressure: 25 bar<br>Model of Differential Cell: H, for setting ranges from 400 mbar to 25 bar<br>switch enclosure: aluminium,copper-free<br>contact version: 1xSPDT, silver contact<br>Unit: bar<br>setting range: 0...2,5 bar<br>Process connection: Adaptor G 1/2 A-M<br>Electrical connection: Adaptor M20x1,5-F<br>Enclosure with plate for wall or direct mounting<br>Diaphragm Material: Inconel 718<br>Set point definition: Set Point not defined<br>Brand: WIKA Instruments Italia<br>Connection: Aluminium alloy<br>DCCH2A |

*© 2023 - WIKA Instruments s.a.r.l.*