Date: 11/04/2023

TW20 P=26.7 mm 1/2 NPT female U=54 mm B=0.260 inch (6.6 mm) SS316/316L

Socket weld Thermowell TW20, solid machined

Item number: 48779031

Quantity: 1 pcs.

Order code: TW20-B-M-2-UD-00054-00045-G3-A-3-0127-0127-ZZ-3-Z00092
Z00092ZZYQ3Z
CERT31-EG3A-BB- - - - - - - - - - - TW-CT2

Overview: TW20 P=26.7 mm 1/2 NPT female U=54 mm B=0.260 inch (6.6 mm) SS316/316L
Welding diameter: 26.7 mm
Connection to thermometer [N]: 1/2 NPT female
Thermowell style: Straight
Head length [H]: 45 mm
Insertion length [U]: 54 mm
Root diameter [Q]: 12.7 mm
Tip diameter [V or F3]: 12.7 mm
Bore size [B or d1]: 0.260 inch (6.6 mm)
Bore depth / stem length (US) [A]: 92 mm
Specifications according to data sheet: TW 95.20

Inspection certificate acc. to DIN EN 10204 3.1
Certificate Language: English and German
Thermowell / protection tube
Material certificate: Wetted parts material (metal contents) with mill certificate incl. chemical analysis

Details: Socket weld Thermowell TW20, solid machined
Specifications according to data sheet: TW 95.20
Thermowell style: Straight
Unit of measure: Metric (mm)
Welding diameter: 26.7 mm (for 3/4 inch pipe)
Connection to thermometer [N]: 1/2 NPT female
Insertion length [U]: 54 mm
Head length [H]: 45 mm
Material: Stainless steel 316/316L
Bore size [B or d1]: 0.260 inch (6.6 mm)
Pressure rating: Class 3000
Root diameter [Q]: 12.7 mm
Tip diameter [V or F3]: 12.7 mm
Bore depth / stem length (US) [A]: 92 mm
Tip thickness [Tt]: 0.250 inch (6.4 mm)
Inspection certificate acc. to DIN EN 10204 3.1

© 2023 - WIKA Instruments s.a.r.l.

Date: 11/04/2023

Certificate Language: English and German
Thermowell / protection tube
Material certificate: Wetted parts material (metal contents) with mill certificate incl. chemical analysis

© 2023 - WIKA Instruments s.a.r.l.