DATASHEET - SWD4-SFL8-12



SWD switch cabinet bushing; 8 pole ribbon cable on 5-pin round cable

Part no. **SWD4-SFL8-12**
174756

General specifications	
Product name	Eaton SWD4 Accessory Switch cabinet bushing
Part no.	SWD4-SFL8-12
EAN	4015081712427
Product Length/Depth	82.4 millimetre
Product height	21 millimetre
Product width	35.2 millimetre
Product weight	0.045 kilogram
Certifications	UL File No.: E29184 CSA File No.: 2324643 UL Category Control No.: NKCR CSA CSA Class No.: 3211-07 IEC/EN 61131-2 UL EN 50178
Product Tradename	SWD4
Product Type	Accessory
Product Sub Type	Switch cabinet bushing
General information	
Degree of protection	IP20 IP20 (according to IEC/EN 60529, EN 50178, VBG 4)
Overvoltage category	II
Pollution degree	2
Product category	SmartWire-DT accessories
Ambient conditions, mechanical	
Constant acceleration	1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations
Constant amplitude	3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations
Drop and topple	50 mm Drop height, Drop to IEC/EN 60068-2-31
Height of fall (IEC/EN 60068-2-32) - max	0.3 m
Mounting position	As required
Shock resistance	15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts
Climatic environmental conditions	
Air pressure	795 - 1080 hPa (operation)
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	55 °C
Ambient storage temperature - min	-40 °C
Ambient storage temperature - max	70 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-3 Dry heat to IEC 60068-2-2
Environmental conditions	Condensation: prevent with appropriate measures
Operating temperature - min	-25 °C
Operating temperature - max	70 °C
Relative humidity	5 - 95 % (non-condensing, IEC/EN 60068-2-30)
Electro magnetic compatibility	
Air discharge	8 kV, according to IEC 61131-2, level 3, ESD
Contact discharge	4 kV, according to IEC/EN 61131-2, Level 2, ESD
Electromagnetic fields	10 V/m at 80 - 1000 MHz (according to IEC/EN 61131-2:2008) 3 V/m at 1.4 - 2 GHz (according to IEC/EN 61131-2:2008) 1 V/m at 2.0 - 2.7 GHz (according to IEC/EN 61131-2:2008)
Radiated RFI	10 V (IEC/EN 61131-2:2008, Level 3)
Electrical rating	

Power loss	1 W
Communication	
Connection type	Connection 1: Plug, 8-pole M12 socket (A-keyed), 5 pole
Input/Output	
Number of insertion cycles	100
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	1 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Meets the product standard's requirements.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Programmable logic controllers PLC (EG000024) / Accessories/spare parts for controls (EC002584)	
Electric engineering, automation, process control engineering / Display and control component / Panel (HMI) / Panel (HMI, accessories) (ecl@ss13-27-33-02-92 [AFX005008])	
Type of electrical accessory/spare part	Plug
Type of mechanical accessory/spare part	Other
Accessory	Yes
Spare part	No

© 04/2023 by Eaton Industries GmbH