DATASHEET - SL7-CB-D-M12A4

Basic module, one-sided vertical mounting, max. 3 modules, M12A

Part no. **SL7-CB-D-M12A4**
177351

Product name	Eaton Moeller® series SL7 Base module
Part no.	SL7-CB-D-M12A4
EAN	4015081718115
Product Length/Depth	84 millimetre
Product height	153 millimetre
Product width	96 millimetre
Product weight	0.241 kilogram
Certifications	IEC/EN 60947-5-1 UL report applies to both US and Canada UL Category Control No.: NKCR CSA-C22.2 No. 94-91 CE CSA-C22.2 No. 14-10 CSA Class No.: NKCR7 UL IEC/EN 60529 UL File No.: E29184 UL 508 Certified by UL for use in Canada
Product Tradename	SL7
Product Type	Base module
Product Sub Type	None
Color	Other
Fitted with:	External fixing holes Cover
Number of modules	Max. 3
Connection to SmartWire-DT	No
Degree of protection	IP66 NEMA 1
Mounting Method	Vertical Floor Bracket
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Product Category	SL signal towers
Rated impulse withstand voltage (Uimp)	2000 V AC
Type	Base module
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	60 °C
Rated insulation voltage (Ui)	250 V
Rated operational voltage	110/120 V AC ± 10 % 24 V AC/DC ± 10 % 230/240 V AC ± 10 %

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Connection module for signal tower (EC001152)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Signal column element, connection module (ecl@ss10.0.1-27-37-12-32 [AKF050014])

Connection type auxiliary circuit	Other
Suitable for tube mounting	No

Suitable for bracket mounting			Yes
Suitable for floor mounting			Yes
Colour			Other
Suitable for AS interface			No

© 04/2023 by Eaton Industries GmbH