Mini CMEL



Technical specifications

IP66 CE

Suitable for the following cable types

Non-armoured cable

Cable with insulated conductors, with no metallic layer of mechanical protection.

Certifications
EN 62444

Continuous operating temperature
-20 °C to + 100 °C

ISO (metric) threadforms
EN 60423 and EN 62444

Material
Body and cap: nickel-plated brass
Sealing ring: nitrile rubber
O-ring: nitrile rubber



Perfectly adapted to industrial environments

- The Mini CMEL ensures the tightness on the cable outer sheath
- Provided with an integrated o-ring
- IP66

* For 'across corners' dimensions, multiply 'across flats' dimensions by 1.1

Description

Our range of metallic industrial cable glands Mini CMEL allows the connection of very small diametre non-armoured cables. Accommodating a nitrile rubber sealing ring, an IP66 as well as a perfect tensile strength are achieved.
Mini CMEL cable glands are provided with ISO 8 and ISO 10 threads.

Powering Business Worldwide

Ordering codes

Mini CMEL - ISO thread

ISO THREAD	CABLE DIAMETER MIN	MAX	ORDER UNIT	CATALOG NUMBER
8 x 1.25	3.0	5.3	20	CAP170804
10 x 1.5	3.5	6.5	20	CAP171004

All dimensions in mm.



Powering Business Worldwide

© 2025 Eaton
All Rights Reserved
August 2025

www.eaton.eu

Eaton is a registered trademark.

All other trademarks are property of their respective owners.