Specifications

Eaton 125D200R

Catalog Number: 125D200R

Eaton Fuse-link, low voltage, 125 A, AC 500 V, D5, 56 x 46 mm, gR, DIN, IEC, ultra rapid



General specifications

Product Name
Eaton Bussmann series low voltage D fuse

Catalog Number
125D200R

EAN
5027590429740

Product Length/Depth
26 mm

Product Height
7.6 mm

Product Width
11 mm

Product Weight
216.6 g

Compliances
CE
RoHS Compliant
CE Marked

Certifications
IEC/EN 60269-3
VDE 0636
IEC 60269
DIN EN 60269-3 (VDE 0636 Part 30)
DIN EN 60269-1 (VDE 0636 Part 10)
DIN VDE 0636-301

Powering Business Worldwide

Product specifications

Type

Fuse

Application

For domestic and general industrial applications

Amperage Rating

125 A

Fuse size

DV

Current type

AC

Breaking capacity

50 kA

Frequency rating - max

62 Hz

Frequency rating - min

45 Hz

Construction size (fuse inserts)

DV

Rated voltage AC

500 V

Class

Class gR

Fuse type

D200R - Ultra rapid

Accessory/spare part type

125GD200 Yellow screw cap gauge piece

Utilization category

gR (general purpose semiconductor protection)

Color

Yellow

Interrupt rating

50 kAIC

Fuse indicator

Non-indicating

Insulated metal gripping lugs (IMGL)

Resources

Brochures

eaton-bussmann-series-d-and-d0-fuses-product-aid-pa132014en-en-us.pdf

Catalogs

CA134002EN

Technical service bulletins

Datasheet - 125D200R

No

Connection

Other

Construction

D5

Construction size

DV

Fuse shape

Bottle

Response time

Ultra rapid

Voltage type

AC

Suitable for

R2/DV Fuse base

Material

White ceramic body

Release characteristic

Super fast (FF)

Voltage rating

500 V

Fuse system (according to IEC 60269)

Other

Rated switching capacity AC

50 kA

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia