HALP161609GE

Terminal box, 160x160x90

The aluminium terminal box range, HALP, with a IP 66, 67 protection degree, is available off the shelf in many different sizes. The HALP range is well suited for indoor and outdoor environments thanks to excellent corrosion resistance. Water and dust are prevented from entering the terminal box, thus eliminating the risk for component failure, and with that, unnecessary downtime.

Feature:
IP 66, 67 IK 08/09

CE UKCA EAC GOST



CHARACTERISTICS	
Height	160 mm
Width	160 mm
Depth	90 mm
Weight (kg)	1.55
Body thickness	4.1 mm
Cover thickness	3.7 mm
Thread for mounting plate	M6
Number of cover screws	4

Item no.: HALP161609GE
EAN no.: 8713574089297

Technical data

Material: Aluminium alloy EN AC-47100.

Gasket: Standard supply fitted with a polyurethane gasket. Silicone, neoprene and EPDM gaskets are available on request.

Temperature resistance: -30 °C to +80 °C.

Protection: IP 66, 67 | IK 09, 08 for HALP050503GE.

Finish: RAL 7001.

Approvals: CE, GOST. For cULus_UL Listed approvals, please contact our sales department.

Delivery: Body and cover are manufactured from aluminum, cover screws are made of stainless steel.

Features

Feature: Aluminium terminal box, available in a wide range of sizes, with a high IP 66, 67 protection degree.

Advantage: Customers can choose terminal boxes that meet their size requirements, off the shelf. The installed components inside the terminal box will be safe and secure due to the high protection degree.

Benefit: Customers can receive terminal boxes with a short delivery time, that match their size requirements which can be installed in both indoor and outdoor environments due to the terminal box's excellent resistance to corrosion. This will also remove any extra costs due to oversizing. Component failure and unnecessary downtime is avoided as water and dust are prevented from entering the terminal box.

Comment: The mounting plate, HMP, has to be ordered separately, in order to complete the installation of the terminal box.