CAT. N° 4 129 11



CONTROL SWITCH SINGLE FUNCTION - 20 A 250 V~ - NO+NC

Pack (number of units)	10
Volume (dm³)	1,619
Weight (g)	610,00

Product characteristics

Maintained contact control switches

- Conform to IEC 60669-1
- Nominal rating 20 A - 250 V~
- Compatible with fluorescent lamps (20 AX)
- Maximum power with self-ballasted lamps (SBL): 250 W
- Accept prong-type supply busbars

Single function control switches

- 1 NO + NC
- Number of modules : 1

General characteristics

CX³ changeover switches, push-buttons, control switches and LED indicators

Documentation

Catalogue pages & additional information

- Description page (p.089)
- Dimensions of din-rail equipment
- CX3 changeover switches, push-buttons, control switches and LED indicators

Agreements & certificates of conformity

- NF-NF012_2631
- OC / CB-FR_709429

Installation & technical data

- F02022EN-03

Environmental product profile

- LGRP-2015-076-V2-EN

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.