EARTHING & NEUTRAL BUSBAR, BRASS, 166 CONNECTIONS

CATALOG NUMBER

EB168



nVent ERIFLEX Connecting, Earthing and Neutral Busbars are used to connect several earthing conductors within a panel and can be used in a variety of different applications including switchgear and control equipment, electrical equipment, for wind and solar power generation and in data centers.

CERTIFICATIONS

FEATURES

- Use to connect several earthing conductors
- Chamfered holes allow for easy connections
- Rigid bar
- RoHS compliant

PRODUCT ATTRIBUTES

- Article Number: 568630
- Material: Brass
- Number of Connections: 166
- Conductor Size, IEC: (166) 1.5 - 4 mm² Stranded
- Ferrule Conductor Size, IEC: (166) 0.75 - 4 mm²
- Conductor Size, UL: (166) #16 - #10 Solid; (166) #10 Stranded
- Depth: 8 mm
- Height: 8 mm
- Width: 1000 mm

A: 6 mm

Unit Weight: 0.45 kg

Complies With: IEC® 61439.1

DIAGRAMS





WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500

Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.