Specifications

Eaton 062655

Catalog Number: 062655

Eaton xEffect Ci Enclosures Switch- & Controlgear Enclosure. Base, smooth sides, HxWxD=250x375x120mm



General specifications

Product Name
Eaton xEffect Ci Enclosures Switch- & Controlgear Enclosure

Catalog Number
062655

EAN
4015080626558

Product Length/Depth
150 mm

Product Height
250 mm

Product Width
375 mm

Product Weight
1.692 kg

Compliances
RoHS conform

Certifications
EN 61439-2
EN 62208

Powering Business Worldwide

Product specifications

Special features

Distance frame for CI45... #110103 Flanges #024355 Smooth sides Without knockouts

Type

Basic enclosure Enclosure bases xEnergy Safety Ci

Features

Cover with overpressure release

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility.

10.13 Mechanical function

Meets the product standard's requirements.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

960 °C

10.2.4 Resistance to ultra-violet (UV) radiation

Not relevant to indoor installations.

10.2.5 Lifting

10 kg per enclosure with support frame and lifting aid met; assembled and secured as per the latest applicable instruction leaflet.

10.2.6 Mechanical impact

IK10

10.2.7 Inscriptions

Meets the product standard's requirements.

Resources

Brochures

eaton-xenergy-safety-ci-enclosure-brochure-br014001en-en-us.pdf

Certification reports

eaton-xeffect-ci-certificate-of-compliance-en-us.pdf

Drawings

eaton-enclosures-enclosure-xenergy-safety-ci-base-dimensions-002.eps

eaton-enclosures-base-xeffect-ci-3d-drawing.eps

Installation instructions

05670392.pdf

Installation videos

xEffect CI stand-alone polycarbonate enclosure

mCAD model

u_ci43x.stp

u_ci43x.dwg

10.3 Degree of protection of assemblies

IP65, with cover

10.4 Clearances and creepage distances

Is the panel builder's responsibility.

10.5 Protection against electric shock

Protection class 2, therefore not applicable.

10.6 Incorporation of switching devices and components

Is the panel builder's responsibility.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Ui = 1000 V AC

10.9.3 Impulse withstand voltage

8 kV

10.9.4 Testing of enclosures made of insulating material

Meets the product standard's requirements.

Accessory/spare part type

Individual enclosure bottoms

Degree of protection

IP65

IK10

Other

Enclosure material

Plastic

Surface protection

Other

Circuit integrity

Other

Base type

Plain

Unit type

Modular system

Built-in depth

200 mm

Heat diss. ambient 35°C delta T:20°C wall mount individ. encl. top (IEC 60890)

19 W

Heat diss. ambient 35°C delta T: 20°C wall mount middle encl. top (IEC 60890)

17 W

Heat diss. ambient 35°C delta T:20°C wall mount starting encl. top (IEC 60890)

18 W

Heat diss. ambient 35°C delta T:35°C wall mount individ. encl. top (IEC 60890)

38 W

Heat diss. ambient 35°C delta T: 35°C wall mount middle encl. top (IEC 60890)

34 W

Heat diss. ambient 35°C delta T:35°C wall mount starting encl. top (IEC 60890)

36 W

Color

Gray

Cover/door model

Closed

Cover/door type

Optional

None

Number of openings (flange plates)

0

Plate thickness (cabinet)

9 mm

Plate thickness (cover/door)

6 mm

RAL-number

7035

Width in number of modular spacings

15

Cable entry type

Top and bottom

Drill as required

Transverse

Mounting method

Surface mounted (plaster)

Number of rows

0

Protection class

II

Number of modules

1

Internal depth

100 mm

Nominal current

1600 A

Number of conduit inlets

0

Suitable for

Outdoor use

Lightning protection

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia