Specifications

Eaton 9702-0201

Catalog Number: 9702-0201

Eaton DG1 Variable frequency drive, 400 V AC, 3-phase, 3.3 A, 1.1 kW, IP20/NEMA0, Brake chopper



General specifications

Product Name
Eaton DG1 variable frequency drive

Catalog Number
9702-0201

EAN
4015081939640

Product Length/Depth
173.5 mm

Product Height
268.7 mm

Product Width
127 mm

Product Weight
2.2 kg

Certifications
CE
Safety requirements: IEC/EN 61800-5
UL File No.: E134360
EAC
UL Category Control No.: NMMS, NMMS7
Specification for general requirements: IEC/EN 61800-2
IEC/EN 61800-3
UL
CUL
C-Tick
RoHS, ISO 9001
UkrSEPRO

Powering Business Worldwide

Catalog Notes
The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request.

Features & Functions

Features

Tool-less swapping of fan

Temperature-controlled fan

Parameterization: Fieldbus

Parameterization: Keypad

Parameterization: Power Xpert inControl

Functions

4-quadrant operation possible

General

Air volume capacity

24 m³/h

Cable length

100 m, screened, maximum permissible, Motor feeder

C3 ≤ 50 m, Radio interference level, maximum motor cable length

C2 ≤ 10 m, Radio interference level, maximum motor cable length

Degree of protection

IP20

NEMA Other

Electromagnetic compatibility

1st and 2nd environments (according to EN 61800-3)

Environmental class

3C2, 3S2 (Air quality)

Fitted with:

Internal DC link

Radio interference suppression filter

Additional PCB protection

Multi-line graphic display

DC link choke

Brake chopper

IGBT inverter

Breaking resistance

Control unit

PC connection

Frame size

FS0

Mounting position

Vertical

Number of slots

2 (expansion)

Overvoltage category

III

Pollution degree

2

Product Category

Variable frequency drives

Protection

Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)

Radio interference class

Optional external radio interference suppression filter for longer motor cable lengths and for use in different EMC environments
C1: with external filter, for conducted emissions only
C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.

Safety function/level

STO (Safe Torque Off, SIL1, PLc Cat 1)

Shock resistance

Mechanical, According to EN 61800-5-1, IEC/EN 60068-2-27
UPS drop test (for weights inside the UPS frame)
Storage and transportation: maximum 15 g, 11 ms (inside the packaging)

Suitable for

Branch circuits, (UL/CSA)

Vibration

Resistance: 5 - 15.8 Hz, Amplitude 1 mm (peak)
Resistance: 5 - 150 Hz, According to EN 61800-5-1, IEC/EN 60068-2-6
Resistance: 15.8 – 150 Hz, 1 g, Maximum acceleration amplitude

Climatic environmental conditions

Altitude

Max. 1000 m
Above 1000 m with 1 % derating per 100 m
Max. 3000 m
Max. 2000 m for Corner Grounded TN Systems

Ambient operating temperature - min

-10 °C

Ambient operating temperature - max

50 °C

Ambient operating temperature at 150% overload - min

-30 °C

Ambient operating temperature at 150% overload - max

50 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

70 °C

Climatic proofing

< 95 average relative humidity (RH), no condensation, no corrosion

Main circuit

Current limitation

0.1 - 2 x IH (CT), motor, main circuit

Efficiency

97.33 % (η)

Heat dissipation at current/speed

27 W at 25% current and 0% speed
30 W at 25% current and 50% speed
31 W at 100% current and 50% speed
35 W at 50% current and 50% speed
38 W at 50% current and 90% speed
42 W at 100% current and 0% speed
46 W at 50% current and 0% speed
52 W at 100% current and 90% speed

Input current ILN at 110% overload

5.5 A

Input current ILN at 150% overload

4.3 A

Leakage current at ground IPE - max

0.2 mA

Mains current distortion

35.3 %

Mains switch-on frequency

Maximum of one time every 60 seconds

Mains voltage - min

380 V

Mains voltage - max

500 V

Operating mode

U/f control
Sensorless vector control (SLV)
Speed control with slip compensation
Torque regulation

Output frequency - min

0 Hz

Output frequency - max

400 Hz

Output voltage (U2)

500 V AC, 3-phase
400 V AC, 3-phase
480 V AC, 3-phase

Overload current IL at 110% overload

4.73 A

Overload current IL at 150% overload

4.95 A

Rated conditional short-circuit current (Iq)

100 kA

Rated control supply voltage

10 V DC (Us, max. 10 mA)

Rated frequency - min

45 Hz

Rated frequency - max

66 Hz

Rated operational current (Ie) at 110% overload

Motor rating

Assigned motor current IM at 400 V, 50 Hz, 110% overload

3.6 A

Assigned motor current IM at 400 V, 50 Hz, 150% overload

2.6 A

Assigned motor current IM at 440 - 480 V, 60 Hz, 150% overload

3 A

Assigned motor current IM at 440/480 V, 60 Hz, 110% overload

3.4 A

Assigned motor current IM at 500 V, 50 Hz, 110% overload

4 A

Assigned motor current IM at 500 V, 50 Hz, 150% overload

2.9 A

Assigned motor power at 460/480 V, 60 Hz

1.5 HP

Assigned motor power at 460/480 V, 60 Hz, 110% overload

2 HP

Apparent power

Apparent power at 400 V

3 kVA

Apparent power at 480 V

3.7 kVA

Braking function

Braking resistance

63 Ω

Braking torque

Adjustable to 150 % (I/Ie), DC - Main circuit
Max. 100 % of rated operational current Ie with external braking resistor - Main circuit
Max. 30 % MN, Standard - Main circuit
Adjustable to 150 %, DC - Main circuit

Switch-on threshold for the braking transistor

850 VDC

4.3 A

Rated operational current (Ie) at 150% overload

3.3 A

Rated operational power at 380/400 V, 50 Hz

1.1 kW

Rated operational power at 380/400 V, 50 Hz, 110% overload

1.5 kW

Rated operational power at 500 V, 50 Hz

1.5 kW

Rated operational power at 500 V, 50 Hz, 110% overload

2.2 kW

Rated operational voltage

480 V AC, 3-phase
400 V AC, 3-phase
500 V AC, 3-phase

Resolution

0.01 Hz (Frequency resolution, setpoint value)

Short-circuit protection rating

10 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring

Starting current - max

200 %, IH, max. starting current (High Overload), For 2 seconds every 20 seconds, Power section

Supply frequency

50/60 Hz

Switching frequency

4 kHz, 1 - 12 kHz adjustable, fPWM, Power section, Main circuit

System configuration type

TN-S, TN-C, TN-C-S, TT, IT

Voltage rating - max

500 VAC

Control circuit

Number of inputs (analog)

2

Number of inputs (digital)

8

Number of outputs (analog)

2

Number of outputs (digital)

1

Number of relay outputs

3 (parameterizable, 2 changeover contacts and 1 N/O, 6 A (240 V AC) / 6 A (24 V DC))

Rated control voltage (Uc)

24 V DC (external, max. 250 mA options incl.)

Communication

Communication interface

BACnet MS/TP, built in
PROFIBUS, optional
SmartWire-DT, optional
Modbus TCP, built in
Ethernet IP, built in
CANopen®, optional
Modbus RTU, built in
DeviceNet, optional

Connection to SmartWire-DT

In conjunction with DXG-NET-SWD SmartWire DT module
Yes

Protocol

BACnet
CAN
DeviceNet
EtherNet/IP
MODBUS
Other bus systems
PROFIBUS
PROFINET IO
TCP/IP

Design verification

Equipment heat dissipation, current-dependent Pvid

61 W

Rated operational current for specified heat dissipation (In)

3.3 A

Static heat dissipation, non-current-dependent Pvs

11.4 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Resources

Application notes

Connecting drives to generator supplies

Load balancing in multi motor applications

Analog I/Os

Smoke Mode and fire mode

Torque control

Real time clock and use of the timers

Starting, stopping and operation

Motor data and V/f curves

Operating at low temperatures

Dual Rating What exactly does that mean?

Digital I/Os

DG1 in pump and fan applications

Electromagnetic compatibility (EMC)

PID controller

Catalogs

Product Range Catalog Drives Engineering

Declarations of conformity

DA-DC-00004861.pdf

DA-DC-00004676

eCAD model

DA-CE-ETN.DG1-343D3EB-C20C

Manuals and user guides

MN040002_EN

mCAD model

DA-CS-dg1_fs0

DA-CD-dg1_fs0

Multimedia

Power XL General Purpose Drives

PowerXL DG1 Variable Frequency Drive - Setup via WebUI

Product notifications

eaton-drives-ecodesign-directive-mz040046en-en.pdf

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Powering Business Worldwide

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia